Date: 22/04/2024

F2822 500 kN ±0.05% Fnom 2.0 ±0.02 mV/V Tens./Com.

SPP-Tension-/compression force transducer, model F2822

Item number: 83806041

Quantity: 1 pcs.

Order code: SPP-F2822-M1550C1A5K010500005XXXXXXXXXXXXXXXXXXXX
66FO5150

Overview: F2822 500 kN ±0.05% Fnom 2.0 ±0.02 mV/V Tens./Com.

Model: F2822
Force direction: tension/compression
Rated force/Rated load: 500 kN
Relative linearity error: ±0.05% Fnom
Output signal: 2.0 ±0.02 mV/V
Electrical connection: Cable output, free wires
Cable length: 5 m Ø5 mm
Ingress Protection IP: IP66
Technical data acc. to datasheet: FO51.50

F28221550086-500KN

Details: SPP-Tension-/compression force transducer, model F2822
Technical data acc. to datasheet: FO51.50
Model: F2822 Tension/compr. force transd. f. material testing,female thread, 0..5kN-0..500kN
Units: kN
Rated force/Rated load: 500 kN
Relative linearity error: ±0.05% Fnom
Force direction: tension/compression
Electrical connection: Cable output, free wires
Cable length: 5 m
Cable diameter: Ø5 mm
Ingress Protection IP: IP66
Output signal: 2.0 ±0.02 mV/V

© 2024 - WIKA Instruments s.a.r.l.