


| | |
|---|---|
| **Product-Nr.** | 156410-01 |
| **EAN:** | 4260556627366 |
| **Model:** | TUBELED_70 EVO DC |




| | |
|---|---|
| Order number: | 156410-01 |
| Model: | TUBELED_70 EVO DC |
| Illuminant: | SMD LED |
| Power consumption: | 48 W |
| Lamp luminous flux: | 7596 lm |
| Lamp luminous efficiency: | 155 lm/W |
| Light colour: | 5600K 3-step MacAdam |
| Number of poles: | 3 |
| Connected load: | 24V DC ± 10% |
| Power supply: | external |
| Connection (connector): | M12 A-coded |
| Degree of protection: | IP67/IP69K |
| Class of protection: | III |
| Glare control: | diffuser film |
| Beam angle (optics): | 100° |
| Operating temperature: | -30 °C - +70 °C (-22 °F - 158 °F) |
| Storage temperature: | -20 °C - +80 °C (-4 °F - 176 °F) |
| Colour rendering (Ra): | >85 |
| Lamps lifetime: | > 100,000 h (L80/B10) |
| Housing material: | Aluminum, glass |
| Height [B] x Width [C]: | 59,5 mm x 70 mm (~2,34“ x ~2,76“) |
| Length [A]: | 1100 mm (~43,31“) |
| Weight (net): | 3000 g (~106 oz) |
| Gross weight: | 3780 g (~133 oz) |
| Risk group (DIN EN 62471): | free group |
| Markings: | CE, UKCA, ETL Listed (5003529) |
| Dimmable: | optional via accessories |
| Mounting accessories: | optional |
| Made in: | Germany |



LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com |
Shop.led2work.com