TERMINAL BOX, 400X600X132, TRANSPARENT COVER, NO MP, ABS, IP66

CATALOG NUMBER

OABP406013TE



This ABS terminal box range, OABP, with a IP 66, 67 protection degree, can be extended in depth. It is available off the shelf in many different sizes. Deeper components may be installed when an extension frame, OPCP-EE, is used. The OABP range is well suited for demanding environments, since water and dust are prevented from entering the terminal box, thus eliminating the risk for component failure, and with that unnecessary downtime.

INDUSTRY STANDARDS

CE UKCA

GOST

IP

FEATURES

Description: ABS box, halogen-free, suitable for indoor use. Low UV radiation resistance.
Material: Body: ABS. Plain cover: ABS. Transparent cover: polycarbonate.
Gasket: Polyurethane gasket integrated in the box cover.
Temperature resistance: -40 °C to +60 °C.
Flammability: UL94 HB.
Protection: IP 66, 67 | IK 06 (-25 °C), IK 07 (+35 °C).
Finish: RAL 7035.
Delivery: Body, cover, cover screws manufactured from polyamide and mounting screws.
The installed components inside the terminal box will be safe and secure due to the high protection degree
Customers can receive terminal boxes with a short delivery time, that match their size requirements
This will also remove any extra costs due to oversizing
Component failure and unnecessary downtime is avoided as water and dust are prevented from entering the terminal box
If necessary, deeper components can be installed when the expansion frame, OPCP-EE, has been mounted.
The mounting plate, OMP, and DIN profiles, DR, have to be ordered separately, in order to complete the installation of the terminal box
The expansion frame, OPCP-EE, should be ordered if a deeper terminal box is required
Inner depth (mm): 115

PRODUCT ATTRIBUTES

Height: 400 mm
Width: 600 mm
Depth: 132 mm

Cover Style: Clear
Max Mounting Depth: 115 mm
Weight: 4.1 kg
Material: ABS
Finish: Smooth
Color: Light Gray
Color Code: RAL 7035

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2024 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.