Specifications

Eaton 207215

Catalog Number: 207215

Eaton Moeller® series T5B On-Off switch, T5B, 63 A, surface mounting, 1 contact unit(s), 2 pole, with black thumb grip and front plate





General specifications

Product Name
Eaton Moeller® series T5B On-off switch

Catalog Number
207215

EAN
4015082072155

Product Length/Depth
240 mm

Product Height
162 mm

Product Width
160 mm

Product Weight
1.039 kg

Certifications
IEC/EN 60947
CSA-C22.2 No. 60947-4-1-14
CSA
CE
UL
IEC/EN 60204
CSA File No.: 012528
CSA Class No.: 3211-07
UL Category Control No.: NLRV
IEC/EN 60947-3
UL 60947-4-1
UL File No.: E36332
VDE 0660
CSA-C22.2 No. 94

Powering Business Worldwide

Catalog Notes
Rated Short-time Withstand Current
(Icw) for a time of 1 second

Product specifications

Product Category

On-Off switch

Actuator color

Black

Actuator function

Maintained

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

UV resistance only in connection with protective shield.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Resources

Brochures

Brochure - T Rotary Cam switch and P Switch-disconnector

Catalogs

P Switch-disconnectors and T Rotary cam switches catalogue CA042001EN

Declarations of conformity

DA-DC-00004925.pdf

DA-DC-00004897.pdf

Drawings

eaton-rotary-switches-t5b-changeover-switch-dimensions.eps

eaton-general-rotary-switch-t0-step-switch-symbol.eps

eaton-rotary-switches-surface-mounting-t0-changeover-switch-3d-drawing.eps

eaton-rotary-switches-front-plate-t0-on-off-switch-symbol-002.eps

eaton-general-totally-insulated-t0-main-switch-symbol.eps

eCAD model

ETN.207215.edz

Installation instructions

IL03801009Z

Installation videos

Eaton's P Switch-disconnectors used in a factory

mCAD model

DA-CD-bauform12

DA-CS-bauform12

Product notifications

MZ008006ZU_Orderform_Customized_Switch.pdf

MZ008005ZU_Orderform_Customized_Switch.pdf

Wiring diagrams

eaton-rotary-switches-on-off-switch-t0-on-off-switch-wiring-diagram-002.eps

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Fitted with:

Black thumb grip and front plate

Operating frequency

1200 Operations/h

Pollution degree

3

Climatic proofing

Damp heat, cyclic, to IEC 60068-2-30
Damp heat, constant, to IEC 60068-2-78

Rated impulse withstand voltage (Uimp)

6000 V AC

Rated operational power star-delta at 500 V, 50 Hz

37 kW

Rated operational power star-delta at 690 V, 50 Hz

22 kW

Rated permanent current at AC-21, 400 V

63 A

Rated permanent current at AC-23, 400 V

63 A

Rated uninterrupted current (Iu)

63 A

Static heat dissipation, non-current-dependent Pvs

0 W

Switching angle

90 °

Switching power at 400 V

30 kW

Voltage per contact pair in series

60 V

Rated operational power at AC-3, 500 V, 50 Hz

22 kW

Device construction

Complete device in housing

Rated short-time withstand current (Icw)

1,3 kA, Contacts, 1 second

1.3 kA

Electrical connection type of main circuit

Screw connection

Design

102

Mounting position

As required

Actuator type

Short thumb-grip

Ambient operating temperature - max

40 °C

Ambient operating temperature - min

-25 °C

Ambient operating temperature (enclosed) - max

40 °C

Ambient operating temperature (enclosed) - min

-25 °C

Assigned motor power at 115/120 V, 60 Hz, 1-phase

3 HP

Assigned motor power at 200/208 V, 60 Hz, 1-phase

7.5 HP

Assigned motor power at 200/208 V, 60 Hz, 3-phase

15 HP

Assigned motor power at 230/240 V, 60 Hz, 1-phase

10 HP

Assigned motor power at 230/240 V, 60 Hz, 3-phase

15 HP

Assigned motor power at 460/480 V, 60 Hz, 3-phase

40 HP

Assigned motor power at 575/600 V, 60 Hz, 3-phase

40 HP

Equipment heat dissipation, current-dependent Pvid

4.5 W

Heat dissipation capacity Pdiss

0 W

Heat dissipation per pole, current-dependent Pvid

4.5 W

Number of auxiliary contacts (change-over contacts)

0

Number of auxiliary contacts (normally closed contacts)

0

Rated conditional short-circuit current (Iq)

2 kA

Overvoltage category

III

Control circuit reliability

1 failure per 100,000 switching operations statistically determined, at 24 V DC, 10 mA)

Degree of protection (front side)

IP65

Number of poles

Two-pole

Mounting method

Surface mounting

Degree of protection

NEMA 12

Suitable for

Ground mounting

Branch circuits, suitable as motor disconnect, (UL/CSA)

Number of switches

1

Safe isolation

440 V AC, Between the contacts, According to EN 61140

Screw size

M6, Terminal screw

Inscription

0-1

Shock resistance

15 g, Mechanical, According to IEC/EN 60068-2-27, Half-sinusoidal shock 20 ms

Lifespan, mechanical

500,000 Operations

Load rating

1.6 x I_e (with intermittent operation class 12, 40 % duty factor)

2 x I_e (with intermittent operation class 12, 25 % duty factor)

1.3 x I_e (with intermittent operation class 12, 60 % duty factor)

Terminal capacity

1 x (1 - 25) mm², flexible with ferrules to DIN 46228

2 x (1.5 - 10) mm², flexible with ferrule to DIN 46228

1 x (2.5 - 35) mm², solid or stranded

2 x (2.5 - 16) mm², solid or stranded

12 - 4 AWG, solid or flexible with ferrule

Switching capacity (main contacts, general use)

63 A, Rated uninterrupted current max. (UL/CSA)

Safety parameter (EN ISO 13849-1)

B10d values as per EN ISO 13849-1, table C.1

Number of auxiliary contacts (normally open contacts)

0

Number of contact units

1

Number of contacts in series at DC-23A, 120 V

3

Number of contacts in series at DC-23A, 24 V

1

Number of contacts in series at DC-23A, 240 V

6

Number of contacts in series at DC-23A, 48 V

2

Number of contacts in series at DC-23A, 60 V

3

Rated breaking capacity at 220/230 V (cos phi to IEC 60947-3)

520 A

Rated breaking capacity at 400/415 V (cos phi to IEC 60947-3)

600 A

Rated breaking capacity at 500 V (cos phi to IEC 60947-3)

480 A

Rated breaking capacity at 660/690 V (cos phi to IEC 60947-3)

340 A

Rated making capacity up to 690 V (cos phi to IEC/EN 60947-3)

800 A

Rated operating voltage (Ue) - max

690 V

Rated operating voltage (Ue) - min

690 V

Rated operational voltage (Ue) at AC - max

690 V

Short-circuit current rating (high fault)

10 kA, SCCR (UL/CSA)

100 A, Class J, max. Fuse, SCCR (UL/CSA)

Short-circuit protection rating

80 A gG/gL, Fuse, Contacts

Rated operational current (Ie) at AC-21, 440 V

63 A

Rated operational current (Ie) at AC-23A, 230 V

63 A

Rated operational current (Ie) at AC-23A, 400 V, 415 V

63 A

Rated operational current (Ie) at AC-23A, 500 V

33 A

Rated operational current (Ie) at AC-23A, 690 V

23.8 A

Rated operational current (Ie) at AC-3, 220 V, 230 V, 240 V

51 A

Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V

41 A

Rated operational current (Ie) at AC-3, 500 V

33 A

Rated operational current (Ie) at AC-3, 660 V, 690 V

17 A

Rated operational current (Ie) at DC-1, load-break switches l/r = 1 ms

63 A

Rated operational current (Ie) at DC-13, control switches L/R = 50 ms

25 A

Rated operational current (Ie) at DC-23A, 120 V

25 A

Rated operational current (Ie) at DC-23A, 24 V

50 A

Rated operational current (Ie) at DC-23A, 240 V

20 A

Rated operational current (Ie) at DC-23A, 48 V

50 A

Rated operational current (Ie) at DC-23A, 60 V

50 A

Rated operational current (Ie) star-delta at AC-3, 220/230 V

63 A

Rated operational current (Ie) star-delta at AC-3, 380/400 V

63 A

Rated operational current (Ie) star-delta at AC-3, 500 V

57.2 A

Rated operational current (Ie) star-delta at AC-3, 690 V

29.4 A

Rated operational current for specified heat dissipation (In)

63 A

Rated operational power at AC-23A, 220/230 V, 50 Hz

18.5 kW

Rated operational power at AC-23A, 400 V, 50 Hz

30 kW

Rated operational power at AC-23A, 500 V, 50 Hz

22 kW

Rated operational power at AC-23A, 690 V, 50 Hz

22 kW

Rated operational power at AC-3, 380/400 V, 50 Hz

22 kW

Rated operational power at AC-3, 415 V, 50 Hz

22 kW

Rated operational power at AC-3, 690 V, 50 Hz

15 kW

Rated operational power star-delta at 220/230 V, 50 Hz

18.5 kW

Rated operational power star-delta at 380/400 V, 50 Hz

30 kW

Tightening torque

35.4 lb-in, Screw terminals

4 Nm, Screw terminals

Uninterrupted current

Rated uninterrupted current Iu is specified for max. cross-section.

Rated Switching Capacity

10 HP at 240 V AC, single-phase

15 HP at 200 V AC, three-phase

15 HP at 240 V AC, three-phase

3 HP at 120 V AC, single-phase

40 HP at 480 V AC, three-phase

40 HP at 600 V AC, three-phase

7.5 HP at 200 V AC, single-phase



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia