Date: 11/04/2023

SA-11; 0 ... 4 bar; 4...20 mA, 2-W

Pressure transmitter for sanitary applications

Item number:	12473678
Quantity:	1 pcs.
Order code:	SA-11-A-BBG-RT-AGM4ZZ-ZZZ W101Z-F2B-GSSAK6 LABEL-PG1DE-ZZZZZ- ZZZZZ
Overview:	SA-11; 0 ... 4 bar; 4...20 mA, 2-W @ 10 ... 30 V DC; Accuracy: 0.5% of span Tri-Clamp DN 1 1/2"; circular connector M12x1, 4-pin UB=1, 0V=3 Specifications according to data sheet: PE 81.80 System fill fluid: KN 77 Synthetic oil Label: WIKA standard without / with Tag-number
Details:	Pressure transmitter for sanitary applications Model SA-11 Specifications according to data sheet: PE 81.80 Wetted parts: stainless steel 1.4435 Case: stainless steel Permissible medium temperature: -20 ... +150 °C (-4 ... +302 °F) Output signal: 4 ... 20 mA, 2-wire Unit: bar Measuring range: 0 ... 4 bar Process connection: Tri-Clamp DN 1 1/2" Accuracy: 0.5% of span Electrical connection: circular connector M12x1, 4-pin Power supply: 10 ... 30 V DC Pin assignment: UB=1, 0V=3 *Made in Germany* on label WIKA standard - specification according to data sheet System fill fluid: KN 77 Synthetic oil Import documentation CIS-States: without Label: WIKA standard without / with Tag-number

© 2023 - WIKA Instruments s.a.r.l.