CONTACTUM

# DDS12188SPMS



Surge Device Spec:
Uc - 275V
In - 10kA
Imax - 20kA
Up - ≤1.2kV
Green (ok) Red (replace) status indicator

12 Way H/Int 100A Sw+2x80A RCD+SPD CU

## General

**Box quantity:** 1
**ABC indicator:** A
**Colour:** White
**Fault current protection (RCD):** Yes

## Technical

**Associated standards:** BS EN 61439-3
**Rated voltage:** 220-250V
**Rated current:** 100A
**Frequency:** 50-60Hz
**Wiring system:** 2 pole
**Ambient operating temperature:** -5 to 40°C (24hour average not exceeding 25°C)
**Width in number of modular spacings:** 20
**Nature of supply:** AC
**Rated fault current:** 30
**DIN-rail:** Yes
**Extension possible:** Yes
**With lock:** Optional
**Type of cover:** Hinged
**Material housing:** steel
**Plate thickness cabinet:** 1.2mm
**Plate thickness door/cover:** 1.2mm
**Mounting method:** Surface
**Number of outgoing ways:** 12

Copyright © 2017 Contactum Limited, Victoria House, 2 Blackmoor Lane, Croxley Green Business Park, Watford, WD18 8GA

**Source URL:** https://www.contactum.co.uk/content/dds12188spms