Date: 11/04/2023

PSD-4-ECO ; 0...25 bar gauge; two switching outputs (PNP)

PSD-4-ECO ; 0...25 bar gauge; two switching outputs (PNP)

Item number: 48801382

Quantity: 1 pcs.

Order code: PSD-4-ECO-D-BG425-026S-2O2DZZS-ULZZ-GSFJ W1011P4E-ZZOSW-

Overview:
PSD-4-ECO ; 0...25 bar gauge; two switching outputs (PNP)
OEM Pressure Switch with Display
Output signal: two switching outputs (PNP)
IO-Link: without
Power supply: 15 ... 32 V DC
Measuring range: 0...25 bar gauge
Process connection: G1/2 B EN 837
Sealing: stainless steel
Permissible medium temperature: -25...+85°C
Electrical connection: circular connector M12x1, 4-pin
pin assignment: U+=1,SP2=2, U-=3, SP1 =4
Overload Safety: 2 x
Accuracy: 1.0% of span
Approvals: cULus
Type of packaging: single packaging
Specifications according to data sheet: PE 81.69

Details:
PSD-4-ECO ; 0...25 bar gauge; two switching outputs (PNP)
OEM Pressure Switch with Display
Output signal: two switching outputs (PNP)
IO-Link: without
Power supply: 15 ... 32 V DC
Measuring range: 0...25 bar gauge
Process connection: G1/2 B EN 837
Sealing: stainless steel
Permissible medium temperature: -25...+85°C
Electrical connection: circular connector M12x1, 4-pin
pin assignment: U+=1,SP2=2, U-=3, SP1 =4
Overload Safety: 2 x
Accuracy: 1.0% of span
Approvals: cULus
Type of packaging: single packaging
Specifications according to data sheet: PE 81.69

© 2023 - WIKA Instruments s.a.r.l.