technical hotline +44 (0)1268 563720

ingress protected IP66 | wiring devices

Switchsocket Outlets, Timer Socket Outlets, and Key Operated Socket Outlets

Socket Outlets

13 AMP
IP66



K56486GRY



K56482BLK



K56488GRY

K56486GRY 1
K56486WHI 1
K56486BLK 1

13A DP
1 GANG
SWITCHED

K56482GRY 1
K56482WHI 1
K56482BLK 1

13A DP
2 GANG
SWITCHED

K56488GRY 1
K56488WHI 1
K56488BLK 1

13A DP SWITCHED
2 GANG
NEON
CLEAR COVER

Fixing holes are for No.8 woodscrews (not supplied).

K56486 has 4 x 20mm entries, 1 on top, bottom and each side and is supplied with an earth terminal in the back box.

2 gang backbox has 5 cable entries, 2 on top and 1 centrally on other 3 sides. Supplied with earth terminals in backbox.

DIMENSIONS:
1 gang: 157 x 110 x 89mm
2 gang: 157 x 175 x 89mm

BS 1363 Pt. 2: 1995

IP66 BS EN 60529: 1992

RCD PROTECTED
13 AMP
IP66



K56485GRY



K56485WHI



K56487GRY

K56485GRY 1
K56485WHI 1
K56485BLK 1

13A SP
1 GANG
WITH ELECTRONIC TIMER MODULE

K56487GRY 1
K56487WHI 1
K56487BLK 1

13A 1 GANG DP
KEY OPERATED SOCKET

Timer Module meets the requirements of IEC 60730-1 and IEC 60730-2-7 Standards



K56301GRY



K56231BLK



K56233WHI

K56301GRY 1
K56301WHI 1
K56301BLK 1

1 GANG DP
30 mA RATED TRIPPING CURRENT
ACTIVE CONTROL CIRCUIT

K56231GRY 1
K56231WHI 1
K56231BLK 1

2 GANG SP
30 mA RATED TRIPPING CURRENT
ACTIVE CONTROL CIRCUIT

K56233GRY 1
K56233WHI 1
K56233BLK 1

2 GANG SP
30 mA RATED TRIPPING CURRENT
PASSIVE CONTROL CIRCUIT

RCD protected sockets are pulsating d.c. and a.c. fault current sensitive.

Fixing holes are for No.8 woodscrews (not supplied).

Supplied with an earth terminal in the back box. The Sentrysocket has 5 entries. Suitable for supply voltage of 240V a.c. 50Hz

Standard Shutters.

DIMENSIONS: 157 x 175 x 89mm

BS 7288: 1990

IP66 BS EN 60529: 1992

13 AMP
IP66



K56480GRY



K56481WHI



K56481BLK

K56480GRY 1
K56480WHI 1
K56480BLK 1

13A 1 GANG
UNSWITCHED

K56481GRY 1
K56481WHI 1
K56481BLK 1

13A 2 GANG
UNSWITCHED

Fixing holes are for No.8 woodscrews (not supplied).

K56480 has 4 x 20mm entries, 1 on top, bottom and each side and is supplied with an earth terminal in the back box.

BS 1363: Pt2: 1995

IP66 BS EN 60529: 1992

K56481 Backbox has 5 cable entries, 2 on top and 1 centrally on other 3 sides. Supplied with earth terminals in backbox.

DIMENSIONS:
1 gang: 157 x 110 x 89mm
2 gang: 157 x 175 x 89mm

BS 1363 Pt.2: 1995

IP66 BS EN 60529: 1992

16 AMP
IP66



K56483GRY



K56483WHI



K56483BLK

K56483GRY 1
K56483WHI 1
K56483BLK 1

16A
1 GANG
2P+E
UNSWITCHED

(NON UK)

Fixing holes are for No.8 woodscrews (not supplied).

K56483 is for use with plugs having right angled cable exit.

DIMENSIONS:
157 x 110 x 89mm

IEC60884-1: 2006

IP66 BS EN 60529: 1992

Masterseal enclosures are manufactured from polycarbonate. This provides an extremely high level of impact resistance. However some chemicals and synthetic oils can harm polycarbonate.

Refer to Technical Hotline for assistance
+44 (0) 1268 563720