MULTI-PURPOSE

SKYTEC ECO NICKEL™

GENERAL HANDLING PU COATED GLOVE WITH RECYCLED POLYESTER

Lightweight general handling glove with PU coating and recycled polyester

FEATURES

- Good abrasion and tear resistance, with a secure grip
- RCS (Recycled claim Standard) certified
- Comfortable with an anatomical shaped fit, allowing excellent freedom of movement and reduction of hand fatigue
- Recommended for precise operations requiring maximum dexterity
- Ideal for detailed assembly, light fabrication and small parts handling



RECYCLED 100 claim standard

LIGHTWEIGHT 15gg LINER

SUITABLE FOR

Typical Industries

- Automotive
- Construction
- Electronics
- Manufacturing

Suitable Applications

- Assembly of Small Components
- Maintenance
- Operating Machinery
- Quality Control
- Second and Final Fix

CERTIFICATION

UK CA CE

CAT II

EN 388:2016 + A1:2018

3131X

See overleaf for explanation

Globus GROUP

MULTI-PURPOSE

SKYTEC ECO NICKEL™

PRODUCT INFORMATION

MATERIALS	LINER:	15 gauge recycled polyester
	COATING:	Polyurethane (PU)
COLOUR	Black/Black	
LENGTH (mm)	250 (size dependent)	
CUFF STYLE	Elasticated knit wrist	

RECOMMENDATIONS FOR USE

- USE: General handling glove. Not suitable for thermal, electrical or chemical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE : Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

ORDERING DETAILS

SIZE	CODE	PACKAGING
6/XS 7/S 8/M 9/L 10/XL 11/XXL	SKG00053BB SKG00053BD SKG00053BF SKG00053BH SKG00053BJ SKG00053BL	10 pairs per paper wrap 120 pairs per case

CERTIFICATION LEGENDS



MECHANICAL HAZARDS EN 388:2016
PERFORMANCE LEVELS*

0-4 0-5 0-4 0-4 A-F P

- 0-4: Abrasion Resistance
- 0-5: Circular Blade Cut Resistance
- 0-4: Tear Resistance
- 0-4: Puncture Resistance
- A-F: Straight Blade Cut Resistance (EN ISO: 13997)
- P: Impact Resistance

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

EUROPE
www.globusgroup.com
E: sales@globus.co.uk
T: +44 (0)161 877 4747
F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA
www.globusgroup.com/gcc
E: gcc@globusgroup.com
T: +971 4 882 9962
F: +971 4 882 9963

GLOBUS AMERICAS
www.globusgroup.com
E: americas@globusgroup.com

Globus GROUP

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES
Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

© 2023 Globus (Shetland) Ltd | SKY-DATA-ECO-NICKEL-0123_2

EU Type-Examination Certificate issued by CCQS Certification Services Limited, Block 1 Blanchardstown Corporate Park, Ballycoolin Road, Blanchardstown, Dublin, D15 AKK1, Ireland (Notified Body No 2834)
UKCA Type-Examination Certificate issued by CCQS UK Ltd. 25 Wilton Rd, Pimlico, London SW1V 1LW, United Kingdom. [UK Approved Body No. 1105].
The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.