

Auxiliary contacts
Ordering information




OS Mini




S00040A
MCB_


S00261A
OA_G


S01163B
OSZ4


S00544A
OESAZX169

Auxiliary contacts

Description	Type	Order number	Units/type [pcs]	Weight [kg]
Auxiliary contacts for OS Mini				
Mounting to the switch mechanism, auxiliary/test contacts. Max. two change over contacts.				
Change over contacts				
 Handle position: Test / 0 — Main contacts: open / open / closed — Aux. / Test contacts N.O.: closed / open / closed	OA4B1C	1SCA022193R0150	1	0.03
Single pole contacts > 3 mm contact gap.				
1 NO 	OA4B10	1SCA022276R9050	1	0.03
1 NC	OA4B01	1SCA022276R9210	1	0.03
Mounting on the side of the switch with aux.contact frame OESAZX 169.				
1NO 	MCB-10	1SCA022150R5110	1	0.03
1NC	MCB-01	1SCA022150R5370	1	0.03

Snap-on mounting on the switch, by using a frame OSZ4. IP20.

NO contacts are provided with a positive opening feature. Units/type = 1 piece. Types _AU have gold plated contacts for harsh environments and low operating voltages.

Description	Type	Order number	Delivery batch [pcs]	Weight /unit [kg]
1 NO 	OA1G10	1SCA022353R4970	10	0.03
1 NC	OA3G01	1SCA022456R7410	10	0.03
1 NO	OA1G10AU	1SCA022436R7910	10	0.03
1 NC	OA3G01AU	1SCA022819R5260	10	0.03

Mounting frames for auxiliary contacts of OS Mini

	Type	Order number	Units/type [pcs]	Weight [kg]
Frame for auxiliary contacts OA1G10 and OA3G01 and for fuse monitor. Max. 6 auxiliary contacts can be fitted.				
Mounting on the left side of the switch	OSZ4	1SCA022530R0200	1	0.06
Frame for MCB-_ auxiliary contacts. Not suitable for side operated switches. Max. 6 auxiliary contacts can be fitted.				
Mounting on the right side of the switch	OESAZX169	1SCA022196R9360	1	0.06