Rittal – The System.

Faster – better – everywhere.

Mini fan – SK 3236.124

Date : Apr 26, 2021

ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Mini fan – SK 3236.124

created: 26.04.2021 build on www.rittal.com/uk-en



Product description

Description:	Compact DC fan for enclosure and component cooling in enclosures.
Supply includes:	Fan Assembly screws Contact hazard protection

Product description

Air throughput (unimpeded air flow):	21 m³/h
Air throughput, unimpeded air flow (without filter mats):	
Air throughput, unimpeded air flow (with filter mats):	
Rated operating voltage:	24 V (DC)
Dimensions:	Width: 60 mm Height: 60 mm Depth: 25.4 mm
Temperature range:	Operation (environment): -20 °C...+70 °C
Power consumption P_{el}:	With DC: 1 W
Noise level:	With DC: 20 dB(A)
eCl@ss 8.0/8.1:	27180716

Packs of:	1 pc(s).
Weight/pack:	0.14 kg
EAN:	4028177637603
Customs tariff number:	84145915
ETIM 7.0:	EC000320
ETIM 6.0:	EC000320
eCl@ss 8.0/8.1:	27180716
eCl@ss 6.0/6.1:	27180716
Product description:	SK Mini fan, 1 W, 24 V (DC), WHD: 60 x 60 x 25.4 mm

Approvals

Approvals:	Approval overview UR
Certificates:	EAC