Date: 24/04/2023

232.30.063 250 bar G1/4B lower mount

Bourdon Tube Pressure Gauges, Safety Pattern

Item number:	9239200
Quantity:	1 pcs.
Order code:	232.30-C-BG525Z-GB-UZEZCZZ-ZZZZZZZ 313D41ZI3W0 Z2Z-IZZZZZZ121ZZ LABEL-PG1DE-ZZZZZ
Overview:	232.30.063 250 bar G1/4B lower mount Measuring System 316 SS Ingress protection: IP 65 class 1.6 Window: polycarbonate Permissible medium temperature: + 200 °C Permissible ambient temperature: -40 … +60 °C Pressure Gauge Standard: International (standard Europe) stop-pin at zero *WIKA* with Serial number Label: WIKA standard without / with Tag-number
Details:	Bourdon Tube Pressure Gauges, Safety Pattern Series EN 837-1 Model: 232.30 Specifications according to data sheet: PM 02.04 Measuring system: stainless steel Case filling: without Nominal size: 063 mm Measuring range: gauge pressure range Scale range: 0...250 bar Process connection: G 1/4 B Connector location: lower mount Window: polycarbonate Pointer: standard pointer Accuracy class: class 1.6 Material pressure element: Measuring System 316 SS Pressure Gauge Standard: International (standard Europe) Manufacturer logo: *WIKA* stop pin on dial: at zero Bourdon Tube Pressure Gauges, Safety Pattern Series EN 837-1 Model: 232.30 Specifications according to data sheet: PM 02.04 Measuring system: stainless steel Case filling: without

© 2023 - WIKA Instruments s.a.r.l.

Nominal size: 063 mm
Measuring range: gauge pressure range
Scale range: 0...250 bar
Process connection: G 1/4 B
Connector location: lower mount
Window: polycarbonate
Pointer: standard pointer
Accuracy class: class 1.6
Overpressure safe: standard
Case material: Stainless steel 1.4301
Case surface: bare
Material pressure element: Measuring System 316 SS
Case filling fluid: prepared for filling
Ingress protection: IP 65
Permissible medium temperature: + 200 °C
Permissible ambient temperature: -40 … +60 °C
Movement: stainless steel
Packaging: single packing
Pressure Gauge Standard: International (standard Europe)
Manufacturer logo: *WIKA*
stop pin on dial: at zero
with Serial number
Permissible ambient temperature: -40 … +60 °C

© 2023 - WIKA Instruments s.a.r.l.