# DATASHEET - T3-4-8294/E

**Changeoverswitches, T3, 32 A, flush mounting, 4 contact unit(s), Contacts: 8, 90 °, maintained, With 0 (Off) position, 1-0-2, Design number 8294**

**Part no.** **T3-4-8294/E**
**002513**

| | |
|---|---|
| Product name | Eaton Moeller® series T3 Changeover switch |
| Part no. | T3-4-8294/E |
| EAN | 4015080025139 |
| Product Length/Depth | 114 millimetre |
| Product height | 54 millimetre |
| Product width | 61 millimetre |
| Product weight | 0.252 kilogram |
| Certifications | CSA-C22.2 No. 60947-4-1-14<br>IEC/EN 60947-3<br>CE<br>CSA File No.: 012528<br>CSA<br>VDE 0660<br>UL 60947-4-1<br>UL<br>UL File No.: E36332<br>IEC/EN 60204<br>CSA Class No.: 3211-05<br>UL Category Control No.: NLRV<br>CSA-C22.2 No. 94<br>IEC/EN 60947 |
| Product Tradename | T3 |
| Product Type | Changeover switch |
| Product Sub Type | None |
| Catalog Notes | Rated Short-time Withstand Current (Icw) for a time of 1 second |
| | |
| Enclosure material | Plastic |
| Fitted with: | 0 (off) position<br>Black thumb grip and front plate |
| Inscription | 1-0-2 |
| Number of poles | 4 |
| | |
| Degree of protection | NEMA 12<br>IP65<br>NEMA 1 |
| Degree of protection (front side) | IP65<br>NEMA 12 |
| Lifespan, mechanical | 500,000 Operations |
| Model | Reverser |
| Mounting method | Flush mounting |
| Mounting position | As required |
| Number of contact units | 4 |
| Operating frequency | 1200 Operations/h |
| Overvoltage category | III |
| Pollution degree | 3 |
| Rated impulse withstand voltage (Uimp) | 6000 V AC |
| Safe isolation | 440 V AC, Between the contacts, According to EN 61140 |
| Safety parameter (EN ISO 13849-1) | B10d values as per EN ISO 13849-1, table C.1 |
| Shock resistance | 15 g, Mechanical, According to IEC/EN 60068-2-27, Half-sinusoidal shock 20 ms |
| Suitable for | Branch circuits, suitable as motor disconnect, (UL/CSA)<br>Front mounting |
| Switching angle | 90 ° |
| Type | Changeover switch |

| | |
|---|---|
| Ambient operating temperature - min | -25 °C |
| Ambient operating temperature - max | 50 °C |
| Ambient operating temperature (enclosed) - min | -25 °C |
| Ambient operating temperature (enclosed) - max | 40 °C |
| Climatic proofing | Damp heat, cyclic, to IEC 60068-2-30<br>Damp heat, constant, to IEC 60068-2-78 |
| | |
| Terminal capacity (flexible with ferrule) | 1 x (0.75 - 4) $mm^2$, ferrules to DIN 46228<br>2 x (0.75 - 4) $mm^2$, ferrules to DIN 46228 |
| Terminal capacity (solid/flexible with ferrule AWG) | 14 - 10 |
| Terminal capacity (solid/stranded) | 2 x (1 - 6) $mm^2$<br>1 x (1 - 6) $mm^2$ |
| Screw size | M4, Terminal screw |
| Tightening torque | 17.7 lb-in, Screw terminals<br>1.6 Nm, Screw terminals |
| | |
| Rated breaking capacity at 220/230 V (cos phi to IEC 60947-3) | 260 A |
| Rated breaking capacity at 400/415 V (cos phi to IEC 60947-3) | 260 A |
| Rated breaking capacity at 500 V (cos phi to IEC 60947-3) | 240 A |
| Rated breaking capacity at 660/690 V (cos phi to IEC 60947-3) | 170 A |
| Rated operational current (Ie) | 32 A at AC-3, 230 V star-delta<br>32 A at AC-3, 500 V star-delta<br>25.5 A at AC-3, 690 V star-delta<br>32 A at AC-3, 400 V star-delta |
| Rated operational current (Ie) at AC-3, 220 V, 230 V, 240 V | 23.7 A |
| Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V | 23.7 A |
| Rated operational current (Ie) at AC-3, 500 V | 23.7 A |
| Rated operational current (Ie) at AC-3, 660 V, 690 V | 14.7 A |
| Rated operational current (Ie) at AC-21, 440 V | 32 A |
| Rated operational current (Ie) at AC-23A, 230 V | 32 A |
| Rated operational current (Ie) at AC-23A, 400 V, 415 V | 32 A |
| Rated operational current (Ie) at AC-23A, 500 V | 26.4 A |
| Rated operational current (Ie) at AC-23A, 690 V | 17 A |
| Rated operational current (Ie) at DC-1, load-break switches l/r = 1 ms | 25 A |
| Rated operational current (Ie) at DC-13, control switches L/R = 50 ms | 20 A |
| Rated operational current (Ie) at DC-21, 240 V | 1 A |
| Rated operational current (Ie) at DC-23A, 24 V | 25 A |
| Rated operational current (Ie) at DC-23A, 48 V | 25 A |
| Rated operational current (Ie) at DC-23A, 60 V | 25 A |
| Rated operational current (Ie) at DC-23A, 120 V | 12 A |
| Rated operational current (Ie) at DC-23A, 240 V | 5 A |
| Rated operational power at AC-3, 380/400 V, 50 Hz | 12 kW |
| Rated operational power at AC-3, 415 V, 50 Hz | 11 kW |
| Rated operational power at AC-3, 690 V, 50 Hz | 11 kW |
| Rated operational power at AC-23A, 220/230 V, 50 Hz | 7.5 kW |
| Rated operational power at AC-23A, 400 V, 50 Hz | 15 kW |
| Rated operational power at AC-23A, 500 V, 50 Hz | 15 kW |
| Rated operational power at AC-23A, 690 V, 50 Hz | 15 kW |
| Rated operational power star-delta at 220/230 V, 50 Hz | 7.5 kW |
| Rated operational power star-delta at 380/400 V, 50 Hz | 15 kW |
| Rated operational power star-delta at 500 V, 50 Hz | 18.5 kW |
| Rated operational power star-delta at 690 V, 50 Hz | 22 kW |
| Rated operational voltage (Ue) at AC - max | 690 V |
| Rated uninterrupted current (Iu) | 32 A |
| Uninterrupted current | Rated uninterrupted current Iu is specified for max. cross-section. |
| | |
| Rated conditional short-circuit current (Iq) | 1 kA |
| Rated short-time withstand current (Icw) | 650 A, Contacts, 1 second |

| | |
|---|---|
| Short-circuit current rating (basic rating) | 5 kA, SCCR (UL/CSA)<br>40A, max. Fuse, SCCR (UL/CSA) |
| Short-circuit current rating (high fault) | 10 kA, SCCR (UL/CSA)<br>40 A, Class J, max. Fuse, SCCR (UL/CSA) |
| Short-circuit protection rating | 35 A gG/gL, Fuse, Contacts |
| | |
| Load rating | 1.6 x I# (with intermittent operation class 12, 40 % duty factor)<br>2 x I# (with intermittent operation class 12, 25 % duty factor)<br>1.3 x I# (with intermittent operation class 12, 60 % duty factor) |
| Number of contacts in series at DC-21A, 240 V | 1 |
| Number of contacts in series at DC-23A, 24 V | 1 |
| Number of contacts in series at DC-23A, 48 V | 2 |
| Number of contacts in series at DC-23A, 60 V | 3 |
| Number of contacts in series at DC-23A, 120 V | 3 |
| Number of contacts in series at DC-23A, 240 V | 5 |
| Switching capacity (main contacts, general use) | 25 A, Rated uninterrupted current max. (UL/CSA) |
| Switching capacity (auxiliary contacts, general use) | 10A, IU, (UL/CSA) |
| Switching capacity (auxiliary contacts, pilot duty) | P600 (UL/CSA)<br>A600 (UL/CSA) |
| Rated making capacity up to 690 V (cos phi to IEC/EN 60947-3) | 320 A |
| Voltage per contact pair in series | 60 V |
| | |
| Assigned motor power at 115/120 V, 60 Hz, 1-phase | 1.5 HP |
| Assigned motor power at 200/208 V, 60 Hz, 1-phase | 3 HP |
| Assigned motor power at 200/208 V, 60 Hz, 3-phase | 3 HP |
| Assigned motor power at 230/240 V, 60 Hz, 1-phase | 3 HP |
| Assigned motor power at 230/240 V, 60 Hz, 3-phase | 3 HP |
| Assigned motor power at 460/480 V, 60 Hz, 3-phase | 7.5 HP |
| Assigned motor power at 575/600 V, 60 Hz, 3-phase | 10 HP |
| | |
| Control circuit reliability | 1 failure per 100,000 switching operations statistically determined, at 24 V DC, 10 mA) |
| Number of auxiliary contacts (change-over contacts) | 0 |
| Number of auxiliary contacts (normally closed contacts) | 0 |
| Number of auxiliary contacts (normally open contacts) | 0 |
| Number of contacts | 8 |
| | |
| Actuator function | Maintained<br>With 0 (Off) position |
| Actuator type | Short thumb-grip |
| | |
| Equipment heat dissipation, current-dependent Pvid | 0 W |
| Heat dissipation capacity Pdiss | 0 W |
| Heat dissipation per pole, current-dependent Pvid | 1.1 W |
| Rated operational current for specified heat dissipation (In) | 32 A |
| Static heat dissipation, non-current-dependent Pvs | 0 W |
| 10.2.2 Corrosion resistance | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | Meets the product standard's requirements. |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | UV resistance only in connection with protective shield. |
| 10.2.5 Lifting | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | Meets the product standard's requirements. |
| 10.3 Degree of protection of assemblies | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | Does not apply, since the entire switchgear needs to be evaluated. |

| | | | |
|---|---|---|---|
| 10.7 Internal electrical circuits and connections | | | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | | | Is the panel builder's responsibility. |
| 10.9.2 Power-frequency electric strength | | | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | | | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | | | Is the panel builder's responsibility. |
| 10.10 Temperature rise | | | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 Electromagnetic compatibility | | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 Mechanical function | | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

## Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Off-load switch (EC001105)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Changeover switch (ecl@ss10.0.1-27-37-14-05 [AKF062013])

| | | | |
|---|---|---|---|
| Model | | | Reverser |
| Number of poles | | | 4 |
| With zero (off) position | | | Yes |
| With retraction in 0-position | | | No |
| Rated permanent current Iu | | A | 32 |
| Rated operation current Ie at AC-3, 400 V | | A | 23.7 |
| Rated operation power at AC-3, 400 V | | kW | 12 |
| Degree of protection (IP), front side | | | IP65 |
| Degree of protection (NEMA), front side | | | 12 |
| Number of auxiliary contacts as normally closed contact | | | 0 |
| Number of auxiliary contacts as normally open contact | | | 0 |
| Number of auxiliary contacts as change-over contact | | | 0 |
| Suitable for floor mounting | | | No |
| Suitable for front mounting | | | Yes |
| Suitable for distribution board installation | | | No |
| Suitable for intermediate mounting | | | No |
| Complete device in housing | | | No |
| Material housing | | | Plastic |
| Type of control element | | | Short thumb-grip |
| Type of electrical connection of main circuit | | | Screw connection |


© 04/2023 by Eaton Industries GmbH