Specifications

Eaton 171335



Catalog Number: 171335

Eaton Moeller® series SL4 Ba15d continuous light module, yellow

General specifications

Product Name
Eaton Moeller® series SL4 Continuous light module

Catalog Number
171335

EAN
4015081678723

Product Length/Depth
43 mm

Product Height
75 mm

Product Width
43 mm

Product Weight
0.037 kg

Certifications
UL Category Control No.: NKCR
UL 508
CSA Class No.: NKCR7
IEC/EN 60947-5-1
CE
UL report applies to both US and Canada
UL File No.: E29184
CSA-C22.2 No. 14-10
Certified by UL for use in Canada
CSA-C22.2 No. 94-91
IEC/EN 60529
UL

Catalog Notes
Without light elements

Powering Business Worldwide

Features & Functions

Color

Yellow

Enclosure color

Black

Functions

Continuous light

Light modules

Filament lamp max. 4 W

Number of modules

Max. 10 (with base for mounting on both sides)

Max. 5 (with standard base)

General

Connection to SmartWire-DT

No

Degree of protection

NEMA 4

IP66

Lifespan, electrical

3,000 h

Light type

Continuous light

Material

Enclosure: Polycarbonate (PC)

Cap: Polycarbonate (PC)

Mounting Method

BA15d lamp socket

Mounting position

As required

Overvoltage category

III

Pollution degree

3

Product Category

SL signal towers

Radiation angle

360 °

Rated impulse withstand voltage (Uimp)

4000 V AC

Shock resistance

Mechanical, According to IEC/EN 60068-2-27

15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Type

Continuous light module

Voltage type

AC/DC

Climatic environmental conditions

Ambient operating temperature - min

-30 °C

Ambient operating temperature - max

60 °C

Climatic proofing

Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

Electrical rating

Leakage current

0.003 A

Power consumption

Max. 4 W with the specified voltages

Rated insulation voltage (Ui)

250 V

Rated operational voltage (Ue) at AC - min

24 V

Rated operational voltage (Ue) at AC - max

250 V

Rated operational voltage (Ue) at DC - min

24 V

Rated operational voltage (Ue) at DC - max

250 V

Resources

Brochures

SL4, SL7, SLC Stack light overview brochure BR047017

Catalogs

eaton-rmq-titan-brochure-br047004en-en-us.pdf

eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf

Declarations of conformity

DA-DC-00004257.pdf

DA-DC-00004253.pdf

Drawings

eaton-operating-sl4-continuous-light-dimensions.eps

eaton-operating-button-sl7-continuous-light-symbol-004.eps

eaton-operating-sl7-continuous-light-symbol.eps

eCAD model

ETN.171335.edz

Installation instructions

IL047005ZU

Installation videos

Signal towers SL4 and SL7

mCAD model

DA-CD-sl4_bfl4

DA-CS-sl4_bfl4

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia