PDWM1500

120° Wall Mount PIR Presence Detector



Features & Benefits

- Switches lights ON when presence and motion is detected in combination with light levels
- Ideal for energy saving installations in the workplace, corridors, offices, toilets etc
- Units Can Be Wired In Parallel (Not Exceeding Total Load)
- Enhanced 120° Detection Zone
- IP55 Environmental Rating (Internal Use Only)

Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Wall Mount
Earth Class Rating	Class II
Operating Temperature	-20°C to 40°C
Ingress Protection Rating	IP55
Setting Type	Dial
Approved Mounting Height (m)	1
Presence Detection (m)	5
Motion Detection (m)	10
Detection Angle	120°
Mounting Hole Centres (mm)	60
Standby Consumption	<1W

Data sheet
PDWM1500

Light / PIR Presence Detectors

Number of Channels	1
Switch rating	420W LED, 1500W Halogen or Fluorescent, 250W Fan
ON Time Adjustment	1 Minute to 30 Minutes. User Adjustable
Lux Level	5 to 1000
Detection Range (M)	10
Permanent ON Facility	Yes (Pulse Override)
Dusk Till Dawn	No
Multiple Unit Support	Yes
Cable Entry(s)	Back Entry

General

Weight (g)	102
Height (mm)	86
Width (mm)	86
Depth (mm)	50
Protruding Depth (mm)	36
Body Construction	Polycarbonate
Product Colour	White
EAN Number	5012483011867
Guarantee Period	3 Years
Trade Tariff Commodity Code	8536508090

Line Diagrams

