Technical Specifications

Self-Retracting Lifeline FALCON

Description:

The self-retracting lifeline Falcon range is the safest, most robust range of composite retractable lifelines on the market.
Tested and approved for horizontal applications
(when used with locking karabiner and a 1m steel anchorage sling 1002897).



References	Description
1011728	Falcon 6,20 m galvanized wire
1011729	Falcon 6,20 m stainless steel cable
1011742	Falcon 10 m galvanized wire
1011743	Falcon 10 m stainless steel cable
1011746	Falcon 15 m galvanized wire
1011747	Falcon 15 m stainless steel cable
1011750	Falcon 20 m galvanized wire
1011751	Falcon 20 m stainless steel cable

The cable is now supplied with double ferrule →



HONEYWELL FALL PROTECTION FRANCE SAS
35-37 rue de la Bidauderie
F - 18100 Vierzon - France
Tel : +33 2 48 52 40 40
Fax : +33 2 48 71 04 97
Web site : www.honeywellsafety.com

Features & benefits :

References	Description		weight	Dimensions
1011728	Falcon 6,20 m galvanized wire	Ø 4,5 mm	4,1 kg	255 x 213 x 101 mm
1011729	Falcon 6,20 m stainless steel cable	Ø 4,5 mm	4,1 kg	255 x 213 x 101 mm
1011742	Falcon 10 m galvanized wire	Ø 4,5 mm	5,0 kg	255 x 213 x 101 mm
1011743	Falcon 10 m stainless steel cable	Ø 4,5 mm	5,0 kg	255 x 213 x 101 mm
1011746	Falcon 15 m galvanized wire	Ø 4,5 mm	6.7 kg	342 x 246 x 101 mm
1011747	Falcon 15 m stainless steel cable	Ø 4,5 mm	6.7 kg	342 x 246 x 101 mm
1011750	Falcon 20 m galvanized wire	Ø 4,5 mm	7.7 kg	342 x 246 x 101 mm
1011751	Falcon 20 m stainless steel cable	Ø 4,5 mm	7.7 kg	342 x 246 x 101 mm

* Highly visible load indicator at the snap hook
* High quality, corrosion resistance components
* Quick-activating braking mechanism stops the fall
* No annual factory re-certification required**
* Dual swivels (unit top and snap hook)
* Lightweight, robust composite unit (torsion relieved)

Housing : high-impact Nylon
Hub : Heat Treated Aluminium
Breaking Mechanism : Stainless Steel and Bronze

Cable lifeline : Ø 4.5 mm in Galvanized or Stainless Steel
Snap hook : Zinc-Plated Steel, Double-Locking Swivel Snap Hook with 22mm gate opening

Temperature: -30°C to +50°C
Breaking Strength : 12 KN
EN 360

**The CE standard requires inspection by a trained end-user competent person, following the Miller Repair Guide.

LAW of 19 MARCH 93
PPE are products classified in category III, mortal risks, and as such they have to be the object of a periodic inspection for less than twelve months at the time of its use by the qualified person.
For more information, please contact our technical team at 02 48 52 40 42 or by e-mail techniserv.hsp@honeywell.com

HONEYWELL FALL PROTECTION FRANCE SAS
35-37 rue de la Bidauderie
F - 18100 Vierzon - France
Tel : +33 2 48 52 40 40
Fax : +33 2 48 71 04 97
Web site : www.honeywellsafety.com