CAT. N° 0 566 05



COMBINED UNIT P17 - WITHOUT RAIL 125X220 - IP44 - 380/415 V~ - 16 A - 3P+E

Pack (number of units)	1
Volume (dm³)	5
Weight (g)	1 046,00

Product characteristics

16 and 32 A sockets - 380 to 415 V~ - 50/60 Hz

- IK 08 according to IEC 62262
- Conform to IEC 60439-1
- Supplied without cable glands
- Self-extinguishing: 650 °C

3P+E - without rail

- 125 x 220 mm
- 16 A - IP 44
- IP 44 according to IEC 60529 and EN 60529

General characteristics

P 17 Tempra combined units LV 16 to 63 A - interlocked switched sockets

Documentation

Catalogue pages & additional information

- Selection chart (p.389)

Installation & technical data

- F00140EN-05

Installation instructions & related documents

- 250046003

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.