PRODUCT-DETAILS

# T5S 630 TMA 500-5000 4p F F InN=100%In

T5S 630 TMA 500-5000 4p F F InN=100%In



## General Information

| | |
|---|---|
| Extended Product Type | T5S 630 TMA 500-5000 4p F F InN=100%In |
| Product ID | 1SDA054489R1 |
| EAN | 8015644555863 |
| Catalog Description | T5S 630 TMA 500-5000 4p F F InN=100%In |
| Long Description | C.BREAKER TMAX T5S 630 FIXED FOUR-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMA R 500 I3=2500...5000 A FULLY RATED NEUTRAL |

## Ordering

| | |
|---|---|
| EAN | 8015644555863 |
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85362090 |

## Dimensions

| | |
|---|---|
| Product Net Width | 186 mm |
| Product Net Height | 205 mm |
| Product Net Depth / Length | 103.5 mm |
| Product Net Weight | 5.8 kg |

## Container Information

| | |
|---|---|
| Package Level 1 Units | 1 piece |
| Package Level 1 Width | 248 mm |
| Package Level 1 Height | 240 mm |
| Package Level 1 Depth / Length | 285 mm |
| Package Level 1 Gross Weight | 5.8 kg |
| Package Level 1 EAN | 8015644555863 |

## Environmental

| | |
|---|---|
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |

## Additional Information

| | |
|---|---|
| Electrical Durability | 5000 cycle<br>60 cycles per hour |
| Mechanical Durability | 20000 cycle<br>120 cycles per hour |
| Number of Poles | 4 |
| Power Loss | at Rated Operating Conditions per Pole 28.8 W |
| Product Main Type | SACE Tmax T |
| Product Name | Moulded Case Circuit Breaker |
| Product Type | CB |
| Rated Current ($I_n$) | Main Circuit 500 A |
| Rated Impulse Withstand Voltage ($U_{imp}$) | 8 kV |
| Rated Insulation Voltage ($U_i$) | 1000 V |
| Rated Operational Voltage | 690 V AC<br>750 V DC |
| Rated Service Short-Circuit Breaking Capacity ($I_{cs}$) | (220 V AC) 85 kA<br>(230 V AC) 85 kA<br>(380 V AC) 50 kA<br>(400 V AC) 50 kA<br>(415 V AC) 50 kA<br>(440 V AC) 40 kA<br>(500 V AC) 30 kA<br>(690 V AC) 25 kA |
| Rated Ultimate Short-Circuit Breaking Capacity ($I_{cu}$) | (220 V AC) 85 kA<br>(230 V AC) 85 kA<br>(380 V AC) 50 kA<br>(400 V AC) 50 kA<br>(415 V AC) 50 kA<br>(440 V AC) 40 kA<br>(500 V AC) 30 kA<br>(690 V AC) 25 kA<br>(250 V DC) 2 Poles in Series 50 kA<br>(500 V DC) 2 Poles in Series 36 kA<br>(750 V DC) 3 Poles in Series 25 kA |
| Rated Uninterrupted Current ($I_u$) | 630 A |
| Release | TMA |
| Release Type | TM |
| Short-Circuit Performance Level | S |
| Standards | IEC |
| Sub-type | T5 |
| Suitable For | T5 |
| Suitable for Product Class | Moulded Case Circuit Breakers |

| | |
|---|---|
| Terminal Connection Type | Fixed Circuit-Breakers Front |
| Test Voltage Max ($U_{test}$) | 3500 V |
| Test Voltage at Industrial Frequency for 1 Minute | 3500 V |
| Version | F |

## Certificates and Declarations (Document Number)

| | |
|---|---|
| Data Sheet, Technical Information | 1SDC210004D0203 |
| Declaration of Conformity - CE | 1SDL000165R0005 |
| Environmental Information | 1SDL000191R0003 |
| Instructions and Manuals | 1SDH000437R0001 |
| Instructions and Manuals (Part 2) | ITSCE-RH0100001 |
| REACH Declaration | LB-DT 18-21D |
| RoHS Information | LB-DT 17-21D |

## Classifications

| | |
|---|---|
| ETIM 4 | EC000228 - Power circuit-breaker for trafo/generator/installation prot. |
| ETIM 5 | EC000228 - Power circuit-breaker for trafo/generator/installation prot. |
| ETIM 6 | EC000228 - Power circuit-breaker for trafo/generator/installation prot. |
| ETIM 7 | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| Object Classification Code | Q |
| UNSPSC | 39121100 |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

## Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax T

