Specifications

Eaton 9702-4103-00P

Catalog Number: 9702-4103-00P

Eaton DG1 Variable frequency drive, 400 V AC, 3-phase, 61 A, 30 kW, IP54/NEMA12, DC link choke



General specifications

Product Name
Eaton DG1 variable frequency drive

Catalog Number
9702-4103-00P

EAN
4015081710928

Product Length/Depth
294 mm

Product Height
630 mm

Product Width
237.7 mm

Product Weight
35.2 kg

Certifications
CSA-C22.2 No. 274-13
EAC
CE
Safety requirements: IEC/EN 61800-5
IEC/EN61800-3
IEC/EN61800-5
RoHS, ISO 9001
UL report applies to both US and Canada
Certified by UL for use in Canada
UL File No.: E134360
C-Tick
CUL
IEC/EN 61800-3
Specification for general requirements: IEC/EN 61800-2
UkrSEPRO
UL
UL Category Control No.: NMMS, NMMS7
UL508

Powering Business Worldwide

Features & Functions

Features

Temperature-controlled fan

Externally accessible fan

Parameterization: Fieldbus

Parameterization: Keypad

Parameterization: Power Xpert inControl

General

Air volume capacity

260 m³/h

Cable length

200 m, screened, maximum permissible, Motor feeder

C3 ≤ 50 m, Radio interference level, maximum motor cable length

C2 ≤ 10 m, Radio interference level, maximum motor cable length

Degree of protection

NEMA 12

IP54

Electromagnetic compatibility

1st and 2nd environments (according to EN 61800-3)

Environmental class

3C2, 3S2 (Air quality)

Fitted with:

Control unit

DC link choke

Additional PCB protection

PC connection

Radio interference suppression filter

Multi-line graphic display

IGBT inverter

Internal DC link

Frame size

FS4

Mounting position

Vertical

Number of slots

2 (expansion)

Overvoltage category

III

Pollution degree

2

Product Category

Variable frequency drives

Protection

Finger and back-of-hand proof, Protection against direct contact

(BGV A3, VBG4)

Radio interference class

Optional external radio interference suppression filter for longer motor cable lengths and for use in different EMC environments
C1: with external filter, for conducted emissions only
C2, C3: depending on the motor cable length, the connected load, and ambient conditions. External radio interference suppression filters (optional) may be necessary.

Safety function/level

STO (Safe Torque Off, SIL1, PLc Cat 1)

Shock resistance

Storage and transportation: maximum 15 g, 11 ms (inside the packaging)
UPS drop test (for weights inside the UPS frame)
Mechanical, According to EN 61800-5-1, IEC/EN 60068-2-27

Suitable for

Branch circuits, (UL/CSA)

Vibration

Resistance: 15.8 – 150 Hz, 1 g, Maximum acceleration amplitude
Resistance: 5 - 15.8 Hz, Amplitude 1 mm (peak)
Resistance: 5 - 150 Hz, According to EN 61800-5-1, IEC/EN 60068-2-6

Climatic environmental conditions

Altitude

Max. 2000 m for Corner Grounded TN Systems
Above 1000 m with 1 % derating per 100 m
Max. 1000 m
Max. 3000 m

Ambient operating temperature - min

-10 °C

Ambient operating temperature - max

50 °C

Ambient operating temperature at 150% overload - min

-30 °C

Ambient operating temperature at 150% overload - max

50 °C

Ambient storage temperature - min

-40 °C

Ambient storage temperature - max

70 °C

Climatic proofing

< 95 average relative humidity (RH), no condensation, no corrosion

Main circuit

Current limitation

0.1 - 2 x IH (CT), motor, main circuit

Efficiency

98.3 % (η)

Heat dissipation at current/speed

169 W at 25% current and 0% speed
280 W at 100% current and 50% speed
314 W at 25% current and 50% speed
414 W at 50% current and 50% speed
445 W at 50% current and 90% speed
479 W at 100% current and 0% speed
711 W at 50% current and 0% speed
777 W at 100% current and 90% speed

Input current ILN at 110% overload

65.7 A

Motor rating

Assigned motor current IM at 400 V, 50 Hz, 110% overload

68 A

Assigned motor current IM at 400 V, 50 Hz, 150% overload

55.2 A

Assigned motor current IM at 440 - 480 V, 60 Hz, 150% overload

52 A

Assigned motor current IM at 440/480 V, 60 Hz, 110% overload

65 A

Assigned motor current IM at 500 V, 50 Hz, 110% overload

65 A

Assigned motor current IM at 500 V, 50 Hz, 150% overload

54 A

Assigned motor power at 460/480 V, 60 Hz, 3-phase

40 HP

Input current ILN at 150% overload

55.7 A

Leakage current at ground IPE - max

8.5 mA

Mains current distortion

31.5 %

Mains switch-on frequency

Maximum of one time every 60 seconds

Mains voltage - min

380 V

Mains voltage - max

500 V

Operating mode

Sensorless vector control (SLV)
U/f control
Torque regulation
Speed control with slip compensation

Output frequency - min

0 Hz

Output frequency - max

400 Hz

Output voltage (U2)

480 V AC, 3-phase
500 V AC, 3-phase
400 V AC, 3-phase

Overload current IL at 110% overload

79.2 A

Overload current IL at 150% overload

91.5 A

Rated conditional short-circuit current (Iq)

100 kA

Rated control supply voltage

10 V DC (Us, max. 10 mA)

Rated frequency - min

45 Hz

Rated frequency - max

66 Hz

Rated operational current (Ie) at 110% overload

Assigned motor power at 460/480 V, 60 Hz, 3-phase, 110 % overload

50 HP

Apparent power

Apparent power at 400 V

49.9 kVA

Apparent power at 480 V

62.4 kVA

Braking function

Braking resistance

6.5 Ω

Braking torque

Max. 100 % of rated operational current Ie with external braking resistor - Main circuit
Adjustable to 150 %, DC - Main circuit
Adjustable to 150 % (I/Ie), DC - Main circuit
Max. 30 % MN, Standard - Main circuit

Switch-on threshold for the braking transistor

850 VDC

Control circuit

Number of inputs (analog)

2

Number of inputs (digital)

8

Number of outputs (analog)

2

Number of outputs (digital)

1

Number of relay outputs

3 (parameterizable, 2 changeover contacts and 1 N/O, 6 A (240 V AC) / 6 A (24 V DC))

Rated control voltage (Uc)

24 V DC (external, max. 250 mA options incl.)

72 A

Rated operational current (Ie) at 150% overload

61 A

Rated operational power at 380/400 V, 50 Hz, 3-phase

30 kW

Rated operational power at 380/400 V, 50 Hz, 3-phase, 110% overload

37 kW

Rated operational power at 500 V, 50 Hz, 3-phase

37 kW

Rated operational power at 500 V, 50 Hz, 3-phase, 110% overload

45 kW

Rated operational voltage

480 V AC, 3-phase

500 V AC, 3-phase

400 V AC, 3-phase

Resolution

0.01 Hz (Frequency resolution, setpoint value)

Short-circuit protection rating

100 A, UL (Class CC or J), Safety device (fuse or miniature circuit-breaker), Power Wiring

Starting current - max

200 %, IH, max. starting current (High Overload), For 2 seconds every 20 seconds, Power section

Supply frequency

50/60 Hz

Switching frequency

3.6 kHz, 1 - 10 kHz adjustable, fPWM, Power section, Main circuit

System configuration type

TN-S, TN-C, TN-C-S, TT, IT

Voltage rating - max

500 VAC

Communication

Communication interface

CANopen®, optional

Modbus TCP, built in

BACnet MS/TP, built in

DeviceNet, optional

Ethernet IP, built in

SmartWire-DT, optional

Modbus RTU, built in

PROFIBUS, optional

Connection to SmartWire-DT

In conjunction with DXG-NET-SWD SmartWire DT module

Yes

Protocol

DeviceNet

TCP/IP

PROFINET IO

Other bus systems

MODBUS

BACnet

CAN

PROFIBUS

EtherNet/IP

Design verification

Equipment heat dissipation, current-dependent Pvid

758 W

Heat dissipation capacity Pdiss

0 W

Heat dissipation per pole, current-dependent Pvid

0 W

Rated operational current for specified heat dissipation (In)

61 A

Static heat dissipation, non-current-dependent Pvs

24.42 W

Heat dissipation details

Operation (with 150 % overload), allow for derating

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the

Resources

Application notes

Load balancing in multi motor applications

Motor data and V/f curves

Operating at low temperatures

Dual Rating What exactly does that mean?

Starting, stopping and operation

DG1 in pump and fan applications

Digital I/Os

Electromagnetic compatibility (EMC)

Analog I/Os

Real time clock and use of the timers

Torque control

Connecting drives to generator supplies

PID controller

Smoke Mode and fire mode

Catalogs

Product Range Catalog Drives Engineering

Declarations of conformity

DA-DC-00004861.pdf

DA-DC-00004676

Drawings

eaton-frequency-inverter-dg1-dimensions-004.eps

eaton-frequency-inverter-dg1-3d-drawing-004.eps

eCAD model

DA-CE-ETN.DG1-34061FN-C54C

Manuals and user guides

MN040002_EN

mCAD model

DA-CD-dg1_fs4

DA-CS-dg1_fs4

Multimedia

PowerXL DG1 Variable Frequency Drive - Setup via WebUI

Power XL General Purpose Drives

Product notifications

eaton-drives-ecodesign-directive-mz040046en-en.pdf

devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia