DATASHEET



IFL 50-385-10/01D

- 3 Cable entry M 20 x 1.5
- Thermoplastic enclosure
- DC 2-wire
- Double-insulated
- Wiring compartment
- Design 385

Data

Ordering data

Product type description	IFL 50-385-10/01D
Article number (order number)	101126029
EAN (European Article Number)	4030661277691
eCl@ss number, version 12.0	27-27-40-01
eCl@ss number, version 11.0	27-27-01-01
eCl@ss number, version 9.0	27-27-01-01
ETIM number, version 7.0	EC002714
ETIM number, version 6.0	EC002714

Approvals - Standards

Certificates	CCC

General data

Standards	DIN VDE 0660-208 EN IEC 60947-5-2
Housing construction form	Block
Installation conditions (mechanical)	not flush

Housing material	Plastic
Gross weight	378 g

General data - Features

Integral system diagnostics, status	Yes
Number of cable wires	2

Mechanical data - Switching distances according EN IEC 60947-5-3

Nominal switching distance S_n	50 mm

Mechanical data - Connection technique

Termination	Screw terminals M20 x 1.5
Cable section, maximum	2 x 1.5 mm²

Mechanical data - Dimensions

Length of sensor	135 mm
Width of sensor	80 mm
Height of sensor	40 mm

Ambient conditions

Degree of protection	IP67
Ambient temperature	-25 ... +70 °C
Protection class	II

Electrical data

Operating current, minimum	5 mA
Rated operating voltage	10 ... 40 VDC
Operating current	200 mA
Switching element	NO contact or NC contact

Protection circuit integrated	inductive interference protection Protection against polarity reversal Surge protection Max. fuse rating
Switching frequency, approx.	50 Hz
Type of voltage range	DC

Electrical data - Digital Output

Voltage drop U_d, maximum	5.5 V
Current at Voltage drop U_d	0.1 A
Design of control elements	Two-wire
Current leakage I_r, maximum	0.5 mA

Status indication

Note (Integral System Diagnostics, status)	yellow LED

Note

Note (General)	Programmable by repositioning the plug-in jumper at the terminal screws Mounting angle HW 385-1 to simplify mounting available

Ordering code

Product type description:
IFL (1)-(2)-(3)(4)(5)(6)(7)

(1)

50	Switching distance 50 mm

(2)

385	Square design, 135 x 80 x 40 mm

(3)

01	Opener (NC)

10	Normally open contact (NO)
10/01	NO contact / NC contact with wiring compartment
11	1 NO contact / 1 NC contact antivalent

(4)

without	Cable
D	DC 2-wire

(5)

Z	Protection class IP67

(6)

N	n-type
P	p-type

(7)

2130	Can be used up to +130 C, without LED switching conditions display


Pictures

Product picture (catalogue individual photo)




ID: kifl5f07
| 1.0 MB | .jpg | 352.778 x 529.167 mm - 1000 x 1500 px - 72 dpi
| 83.9 kB | .png | 74.083 x 111.125 mm - 210 x 315 px - 72 dpi
| 69.3 kB | .jpg | 82.197 x 123.472 mm - 233 x 350 px - 72 dpi

Dimensional drawing basic component




ID: 1ifl5g05
| 30.5 kB | .cdr |
| 14.2 kB | .png | 74.083 x 51.153 mm - 210 x 145 px - 72 dpi
| 166.3 kB | .jpg | 352.778 x 243.769 mm - 1000 x 691 px - 72 dpi

Diagram



ID: id2ak03
| 31.0 kB | .cdr |
| 46.0 kB | .jpg | 352.778 x 144.639 mm - 1000 x 410 px - 72 dpi
| 2.4 kB | .png | 74.083 x 30.339 mm - 210 x 86 px - 72 dpi

Operating principle



ID: sifldd01
| 53.6 kB | .ai | 297 x 210.002 mm - 841 x 595 px - 72 dpi
| 50.1 kB | .jpg | 352.778 x 149.578 mm - 1000 x 424 px - 72 dpi
| 1.4 kB | .png | 74.083 x 31.397 mm - 210 x 89 px - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, 42279 Wuppertal
The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.
Generated on: 11/01/2024, 10:29