Laserliner®

VideoFlex G3 Ultra

SnakeCamera G3 10 m

ø 9 mm

10 m
DOF 1...6 cm



Professional video inspection system for visually inspecting areas that are difficult to access – also over great distances

Rev 0915









Camera head (ø 9 mm) with LED-Lighting



3.5" TFT colour display

- **The camera head at a FlexCamera** transfers pictures directly to a LCD-Monitor.
- **Problem locating:** the camera indicates what is behind or in objects, walls circuits or cables etc. even under worst light conditions, due to the LED-lighting.
- **REC-Function:** still picure and video can be **recorded** for a later analysis.
- **Waterproof camera head and cable**
- **Ideal for difficult accessibly areas** due to the small measuring head (ø 9 mm)
- **Camera unit can be replaced** to suit application
- Powerful object lighting thanks to **4 high-performance LEDs**
- **Extraneous light reduction:** contrasty LC-Display which provides an optimum display even under light irridation.
- External monitors operated via **TV Out connection**
- **Formattable SDHC-Card**
- **Rotation:** The manual image rotation function enables the image to be rotated by 180° on the monitor.
- **Mirror function** for correcting mirror-inverted images.

TECHNICAL DATA

CAMERA HEAD / CABLE ø 9 mm, IP 68 (immersion depth 2 m, 60 min.)
CAMERA FOCUS F1 cm - F6 cm
SCREEN TYPE 3.5" TFT colour display
CAMERA RESOLUTION 640 x 480 pixel
RESOLUTION DISPLAY 320 x 240 pixel
RESOLUTION PICTURE / VIDEO 720 x 480 pixel
FORMAT PICTURE / FORMAT VIDEO JPEG / AVI
LED 10 luminosity degrees
ZOOM 1.5 x digital zoom in 10% steps
MEMORY Supports up to max. 8 GB SDHC card
LENGTH OF FLEX CABLE 10 m
PORT Mini USB
CONNECTIONS Micro-SD, Analog-video
POWER SUPPLY Li-Ion pack battery 3.7V / 1.7Ah / 5V / 1A power supply unit
CHARGING TIME approx. 4 h
OPERATING TIME approx. 4 h
OPERATING TEMPERATURE 0°C ... 45°C
STORAGE TEMPERATURE -10°C ... 60°C
WEIGHT (incl. batteries and flexcamera) 1.6 kg



VideoFlex G3 Ultra
inclusive carrying case
+ SnakeCamera G3 10 m
+ TopClips G3
+ TopGuide G3
+ Li-ion battery pack
+ Power supply unit/charger with internal adapter
+ USB cable
+ 4 GB micro-SD card
+ Video cable

Packing dimension (W x H x D)
450 x 375 x 125 mm

ARTICLE	ARTICLE NO.	EAN CODE	PU
VideoFlex G3 Ultra	082.210A	4 021563 695003	2

CAMERA 640 x 480 pixel · LED LIGHT · IP68
DISPLAY 320 x 240 pixel · 3.5" LCD · 180° · ZOOM 1,5x
REC · SD · USB
RECHARGE · HARD

UMAREX GmbH & Co. KG · Donnerfeld 2 · 59757 Arnsberg · Germany · Tel. +49 2932 638-300 · Fax +49 2932 638-333 · laserliner@umarex.de · www.laserliner.com