PRODUCT-DETAILS

GAF750-10-11-70

GAF750-10-11 100-250V 50/60Hz / 100-250V DC Contactor



General Information

Extended Product Type	GAF750-10-11-70
Product ID	1SFL637025R7011
EAN	7320500408803
Catalog Description	GAF750-10-11 100-250V 50/60Hz / 100-250V DC Contactor
Long Description	A 3-pole Contactor suitable for DC-1 applications where all three poles must be connected in series in a 1-pole configuration up to max 1000 VDC. Operated with wide control voltage range 100-250 V, AC/DC

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads

EPLAN Data	9AAC171153_EPLAN
Data Sheet, Technical Information	1SBC100214C0202
Data Sheet, Technical	1SAC200017M0002

© 2025 ABB. All rights reserved.

Information (Part 2)	
Instructions and Manuals	1SFC101045M9701
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Product Net Width	210 mm
Product Net Depth / Length	242 mm
Product Net Height	283 mm
Product Net Weight	14 kg
Dimension Diagram	53540919-60

Technical

Number of Main Contacts NO	1
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	1
Number of Auxiliary Contacts NC	1
Number of Poles	1P
Rated Operational Voltage	Main Circuit 1000 V
Conventional Free-air Thermal Current (I_{th})	acc. to IEC 60947-4-1, Open Contactors Θ = 40 °C 1050 A
Rated Operational Current DC-1 (I_e)	(1000 V) 3 Poles in Series, 40 °C 1050 A (1000 V) 3 Poles in Series, 55 °C 875 A (1000 V) 3 Poles in Series, 70 °C 720 A (220 V) 3 Poles in Series, 40 °C 1050 A (220 V) 3 Poles in Series, 55 °C 875 A (220 V) 3 Poles in Series, 70 °C 720 A (400 V) 3 Poles in Series, 40 °C 1050 A (400 V) 3 Poles in Series, 55 °C 875 A (400 V) 3 Poles in Series, 70 °C 720 A (600 V) 3 Poles in Series, 40 °C 1050 A (600 V) 3 Poles in Series, 55 °C 875 A (600 V) 3 Poles in Series, 70 °C 720 A
Rated Insulation Voltage (U_i)	acc. to UL/CSA 1000 V
Rated Impulse Withstand Voltage (U_{imp})	Main Circuit 8 kV
Mechanical Durability	3 million
Maximum Mechanical Switching Frequency	300 cycles per hour
Coil Operating Limits	(acc. to IEC 60947-4-1) 0.85 x Uc Min. ... 1.1 x Uc Max. (at θ ≤ 70 °C)
Rated Control Circuit Voltage (U_c)	50 Hz 100 ... 250 V 60 Hz 100 ... 250 V DC Operation 100 ... 250 V
Coil Consumption	Holding at Max. Rated Control Circuit Voltage 50 Hz 12 V·A Holding at Max. Rated Control Circuit Voltage 60 Hz 12 V·A Holding at Max. Rated Control Circuit Voltage DC 5.5 V·A Holding at Max. Rated Control Circuit Voltage DC 4.5 W Pull-in at Max. Rated Control Circuit Voltage 50 Hz 850 V·A Pull-in at Max. Rated Control Circuit Voltage 60 Hz 850 V·A Pull-in at Max. Rated Control Circuit Voltage DC 950 V·A
Power Loss	at Rated Operating Conditions per Pole 50 W
Connecting Capacity Main Circuit	Bar 52 mm² Bar 50 mm² Rigid Al-Cable 300 mm² Rigid Al-Cable 3x185 mm² Rigid Cu-Cable 300 mm² Rigid Cu-Cable 3x185 mm²
Connecting Capacity	Flexible with Ferrule 2x 0.75 ... 2.5 mm²

© 2025 ABB. All rights reserved.

Auxiliary Circuit	Flexible with Insulated Ferrule 2x 0.75 ... 2.5 mm² Flexible 2x0.75 ... 2.5 mm² Solid 2 x 1 ... 4 mm² Stranded 2 x 1 .... 4 mm²
Connecting Capacity	Bar 52 mm² Rigid Al-Cable 3x185 mm² Rigid Cu-Cable 3x185 mm²
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP00
Connecting Terminals (delivered in open position) Main Poles	M 3.5 (+,-) pozidriv 2 screw with cable clamp
Recommended Screw Driver	Main Circuit M12 Control Circuit Pozidriv 2 Control Circuit M3.5
Tightening Torque	Cable Lug 45 N·m Main Circuit 45 N·m
Terminal Type	Main Circuit: Bars
Suitable for Product Class	Block ContactorsBlock Contactors
Product Name	Block Contactor

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Main Circuit 1000 V
General Use Rating UL/CSA	(1000 V DC) 900 A (440 V DC) 900 A (600 V DC) 900 A

Environmental

Ambient Air Temperature	Close to Contactor Fitted with Thermal O/L Relay (0.85 ... 1.1 Uc) -25 ... 50 °C Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 Uc) -40 ... 70 °C Close to Contactor for Storage -40 ... 70 °C Operation -40 ... 70 °C Storage -40 ... +70 °C
Maximum Operating Altitude Permissible	Without Derating 3000 m
Resistance to Shock acc. to IEC 60068-2-27	Shock Direction: A 5 g Shock Direction: B1 5 g Shock Direction: B2 5 g Shock Direction: C1 5 g Shock Direction: C2 5 g

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2021-006202
RoHS Declaration	2CMT2021-006277
RoHS Information	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	2CMT2023-006525
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

CB Certificate	SEMKO_SE-70018
CQC Certificate	CQC2013010304595900
Declaration of Conformity - CCC	2020980304001858

© 2025 ABB. All rights reserved.

Declaration of Conformity - CE	2CMT003517
Declaration of Conformity - UKCA	2CMT2020-006118
EAC Certificate	9AKK107046A8618
UL Certificate	20130524-E73397
UL Listing Card	UL E73397

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	280 mm
Package Level 1 Depth / Length	375 mm
Package Level 1 Height	310 mm
Package Level 1 Gross Weight	15 kg
Package Level 1 EAN	7320500408803

External Classifications and Standards

Object Classification Code	Q
ETIM 7	EC002552 - Power contactor, DC switching
ETIM 8	EC002552 - Power contactor, DC switching
ETIM 9	EC002552 - Power contactor, DC switching
eClass	V11.0 : 27371018
UNSPSC	39121529
IDEA Granular Category Code (IGCC)	4763 >> Power contactor, DC switching
E-Number (Finland)	3709746

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors → GA Contactors → GAF750



© 2025 ABB. All rights reserved.