Rittal – The System.

Faster – better – everywhere.

Electric condensate evaporator – SK 3301.505

Date : Apr 26, 2021

ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Electric condensate evaporator – SK 3301.505

created: 26.04.2021 build on www.rittal.com/uk-en



Product description

Description:	For external mounting on the enclosure. For use with all enclosure cooling units and air/water heat exchangers (wall-mounted).
Benefits:	Suitable for international use thanks to multi-voltage support
Colour:	RAL 7035
Supply includes:	Electric condensate evaporator, ready to connect.

Product description

Evaporation performance:	230 V: 3,5 l/d 115 V: 3.0 l/d
Rated operating voltage:	115 V - 230 V, 1~, 50 Hz/60 Hz
Dimensions:	Width: 400 mm Height: 129 mm Depth: 105 mm
Temperature range:	Operation (environment): +5 °C...+60 °C
eCl@ss 8.0/8.1:	27180715
Packs of:	1 pc(s).
Weight/pack:	1.7 kg

EAN:	4028177695528
Customs tariff number:	84189910
ETIM 7.0:	EC002009
ETIM 6.0:	EC002009
eCl@ss 8.0/8.1:	27180715
eCl@ss 6.0/6.1:	27180715
Product description:	SK Electric condensate evaporator, 115-230 V, 1~, 50/60 Hz, WHD: 400 x 129 x 105 mm

Approvals

Certificates:	EAC
Declarations:	Declaration of conformity