Date: 11/04/2023

A52.100/1, 0...250°C, 300x8mm

Bimetal Thermometer, Industrial Series

Item number:	3569420
Quantity:	1 pcs.
Order code:	A52.100-1-C1M-BS-C300GZZ-Z-ZZZ TD FZZVC-AZ1ZZZZZZZZZZ
Overview:	A52.100/1, 0...250°C, 300x8mm Process connection: plain, with neck to fit thermowell (thermowell necessary for mounting) flat instrument glass *WIKA*
Details:	Bimetal Thermometer, Industrial Series Specifications according to data sheet: TM 52.01 Accuracy class: class 1 per EN 13190 Case: stainless steel Stem material: stainless steel Model: A52.100, nominal size 100, location of stem centre back Connection design: 1, plain stem Scale range: 0 °C ... 250 °C Process connection: plain, with neck to fit thermowell (thermowell necessary for mounting) Stem diameter: 8 mm Insertion length L1: 300 mm norm-mark on dial: *EN 13190* accuracy class on dial: *Cl.1* Bimetallic thermometer, for industrial applications A52L Specifications according to data sheet: TM 52.01 Accuracy class: class 1 per EN 13190 Case: stainless steel Stem material: stainless steel Model: A52.100, nominal size 100, location of stem centre back Connection design: 1, plain stem Scale range: 0 °C ... 250 °C Process connection: plain, with neck to fit thermowell (thermowell necessary for mounting) Stem diameter: 8 mm Insertion length L1: 300 mm Window: flat instrument glass Case: Stainless steel Ingress protection: IP 43 Manufacturer logo: *WIKA* Stem material: stainless steel

© 2023 - WIKA Instruments s.a.r.l.