PERFORMANCE MADE SMARTER



Pt100 converter - isolated

3112

- Excellent accuracy, better than 0.05% of span
- Slimline housing of 6 mm
- Excellent EMC performance and 50/60 Hz noise suppression
- Selectable < 30 ms / 300 ms response time
- Pre-calibrated temperature ranges selectable via DIP-switches

Application

- The 3112 temperature converter measures a standard 2-, 3- or 4-wire Pt100 temperature sensor, and provides an isolated analog voltage or current output.
- High 3 port isolation provides surge suppression and protects the control system from transients and noise.
- The 3112 can be mounted in the safe area or in Zone 2 / Division 2 areas.
- Approved for marine applications.

Technical characteristics

- Flexibly powered by 24 VDC (±30%) via power rail or connectors.
- < 30 ms fast response time with simultaneous sensor error detection when selected.
- Selectable 300 ms response time when signal dampening is needed.
- Excellent conversion accuracy in all available ranges, better than 0.05% of span.
- Meeting the NAMUR NE21 recommendations, the 3112 provides top measurement performance in harsh EMC environments.
- The device meets the NAMUR NE43 standard defining out of range and sensor error output values.
- A visible green LED indicates operational status of the unit and the input sensor.
- All terminals are protected against overvoltage and polarity error.
- High galvanic isolation of 2.5 kVAC.
- Excellent signal/noise ratio of > 60 dB.

Mounting / installation / programming

- Selectable DIP-settings for easy configuration of more than 1000 factory calibrated measurement ranges.
- The narrow 6 mm housing allows up to 165 units to be mounted per meter of DIN rail, without any air gap between units.
- Wide ambient temperature range of -25...+70°C.

Applications



This page is automatically generated on the basis of information provided on www.prelectronics.com and affiliated websites. It is provided to you as a service and for information purpose only. While we have attempted to maintain the information as accurately as possible, the page may contain errors or omissions for which we disclaim any and all liability

Order

Type	Version	
3112	With power rail connector / terminals	:-
	Supplied via terminals	:-N

Example: 3112-N

Environmental Conditions

Operating temperature ..... -25°C to +70°C
Storage temperature ..... -40°C to +85°C
Calibration temperature ..... 20...28°C
Relative humidity ..... < 95% RH (non-cond.)
Protection degree IP20
Installation in ..... Pollution degree 2 & meas. / overvoltage cat. II

Mechanical specifications

Dimensions (HxWxD) ..... 113 x 6.1 x 115 mm
Weight approx. ..... 70 g
DIN rail type ..... DIN EN 60715/35 mm
Wire size ..... 0.13...2.5 mm^2 / AWG 26...12 stranded wire
Screw terminal torque ..... 0.5 Nm
Vibration ..... IEC 60068-2-6
2...25 Hz ..... ±1.6 mm
25...100 Hz ..... ±4 g

Common specifications

Supply

Supply voltage ..... 16.8...31.2 VDC
Max. required power ..... 0.70 W
Max. power dissipation ..... 0.70 W

Isolation voltage

Isolation voltage, test / working ..... 2.5 kVAC / 300 VAC (reinforced)
Zone 2 / Div. 2 ..... 250 VAC

Response time

Response time (0...90%, 100...10%) ..... < 30 ms / 300 ms (selectable)
Accuracy ..... Better than 0.05% of selected range
Signal / noise ratio ..... Min. 60 dB
Programming ..... DIP-switches
Signal dynamics, input ..... 23 bit
Signal dynamics, output ..... 18 bit
EMC immunity influence ..... < ±0.5% of span
Extended EMC immunity: NAMUR NE21, A criterion, burst ..... < ±1% of span
Incorrect DIP-switch setting identification ..... 0 V / 0 mA output; LED 0.5 s / 1 Hz

Input specifications

RTD input

Temperature range, Pt100 ..... -200...+850°C
Min. measurement range (span) ..... 10°C
Accuracy: the greater of ..... Better than 0.05% of span or 0.1°C
Temperature coefficient: the greater of ..... 0.02°C/°C or ≤ ±0.01%/°C
Sensor current ..... < 150 µA
Sensor cable resistance ..... < 50 Ω per wire
Effect of sensor cable resistance (3-/4-wire) ..... < 0.002 Ω / Ω
Sensor error detection ..... Yes - selectable via DIP-switch
Broken sensor detection ..... > 800 Ω
Shorted sensor detection ..... < 18 Ω

Output specifications

Common output specifications

Updating time ..... 10 ms

Current output

Signal range ..... 0...23 mA
Programmable signal ranges ..... 0 / 4...20 mA
Sensor error indication (0...20 mA) ..... 0 mA or 23 mA / OFF
Sensor error indication (4...20 mA) ..... 3.5 mA or 23 mA / acc. to NAMUR NE43 or OFF
Load (@ current output) ..... ≤ 600 Ω
Load stability ..... ≤ 0.01% of span / 100 Ω
Current limitation @ low output load ..... < 60 mA peak / < 4 mA average

Voltage output

Programmable signal ranges ..... 0/1...5 and 0/2...10 V
Sensor error indication ..... 0 V / 10% above the max. / none
Open output ..... < 18 V

I.S. / Ex marking

ATEX ..... II 3 G Ex nA IIC T4 Gc
IECEx ..... Ex nA IIC T4 Gc
FM, US ..... Cl. I, Div. 2, Gp. A, B, C, D T4 or Cl. I, Zone 2, AEx nA IIC T4
FM, CA ..... Cl. I, Div. 2, Gp. A, B, C, D T4 or Cl. I, Zone 2, Ex nA IIC T4

Observed authority requirements

EMC 2014/30/EU
LVD 2014/35/EU
RoHS 2011/65/EU
EAC ..... TR-CU 020/2011

Approvals

ATEX 2014/34/EU ..... KEMA 10ATEX0147 X
IECEx ..... KEM 10.0068X
FM ..... FM17US0004X / FM17CA0003X
DNV-GL Marine ..... Stand. f. Certific. No. 2.4
UL ..... UL 61010-1