DISPOSABLE PROTECTION

CHEMICAL PROTECTION

SKYTEC | TX925™

ORANGE SINGLE USE GLOVE WITH GRIP PATTERN, 100% NITRILE, POWDER FREE, 240MM LONG

High performance, powder-free, orange nitrile single use glove with diamond grip pattern technology. Provides outstanding grip performances and chemical protection.

FEATURES

- High quality nitrile, soft and durable
- Palm thickness 0.23mm (9mil), weight: 8.5g size M
- High resistance to penetration and projections of many chemicals
- Diamond grip pattern technology on both side offering outstanding grip properties in all conditions
- Powder-free, latex free, non-sterile, AQL 1.5
- Chlorinated inside to offer more comfort and reduce friction when donning
- Antistatic properties due to inherent antistatic properties of nitrile
- Lasts up to 5 times longer than regular single use gloves in industrial applications
- Ambidextrous for easy and quick donning



SUITABLE FOR

Typical Industries

- Aerospace
- Chemical
- Electronics
- Automotive
- Manufacturing
- Oil and Gas

Suitable Applications

- Chemical Handling
- Handling Oily Components
- Light Assembly
- Engineering
- Repair and Finishing

CERTIFICATION

	CAT III	EN ISO 374-1:2016/Type B	EN ISO 374-5:2016	
UKCA	CE			
0321	2777	KOPT	Virus	

See overleaf for explanation

Globus GROUP

DISPOSABLE PROTECTION

CHEMICAL PROTECTION

SKYTEC® | TX925™

PRODUCT INFORMATION

MATERIALS	LINER:	Nitrile
	COATING:	–
COLOUR	Orange	
LENGTH (mm)	240	
CUFF STYLE	Beaded	

ORDERING DETAILS

SIZE	CODE	PACKAGING
7/S 8/M 9/L 10/XL 11/XXL	SKG00925GD SKG00925GF SKG00925GH SKG00925GJ SKG00925GL	100 singles per box (90 singles on size XXL) 10 boxes per case

RECOMMENDATIONS FOR USE

- USE: Single use glove. Not suitable for mechanical, thermal, heat, electrical, heavy chemical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

CERTIFICATION LEGENDS

RESISTANCE TO CHEMICAL PERMEATION - EN ISO 374:2016

CODE	CHEMICAL	CODE	CHEMICAL
A	Methanol	J	n-Heptane
B	Acetone	K	Sodium hydroxide 40%
C	Acetonitrile	L	Sulphuric acid 96%
D	Dichloromethane	M	65% Nitric acid
E	Carbon Disulfide	N	99% Acetic acid
F	Toluene	O	25% Ammonium hydroxide
G	Diethylamine	P	30% Hydrogen peroxide
H	Tetrahydrofurane	S	40% Hydrofluoric acid
I	Ethyl acetate	T	37% Formaldehyde

TYPE OF GLOVES	BREAKTHROUGH TIME
A	≥30 min for at least 6 chemicals
B	≥30 min for at least 3 chemicals
C	≥10 min for at least 1 chemical

PROTECTION AGAINST MICRO-ORGANISMS EN 374-5

VIRUS = Glove has passed ISO 16604: 2004 (method B)

FOOD CONTACT DIRECTIVE EC 10/2011

EUROPE

www.globusgroup.com

E: sales@globus.co.uk
T: +44 (0)161 877 4747
F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com
T: +971 4 882 9962
F: +971 4 882 9963

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES

©2023 Globus (Shetland) Ltd | SKY-DATA-TX925-0323_1

EU Type-Examination Certificate issued by SATRA Technology Europe Limited. Bracetown Business Park. Clonee. D15YN2P. Republic of Ireland. (Notified Body No. 2777)

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.