DATASHEET - SL4-PIB-T-800

Base module; 800 mm aluminum tube

Part no. **SL4-PIB-T-800**
178461

Product name	Eaton Moeller® series SL4 Base module
Part no.	SL4-PIB-T-800
EAN	4015081737642
Product Length/Depth	43 millimetre
Product height	899 millimetre
Product width	43 millimetre
Product weight	0.8 kilogram
Certifications	IEC/EN 60529 IEC/EN 60947-5-1
Product Tradename	SL4
Product Type	Base module
Product Sub Type	None
Color	Other
Fitted with:	Aluminum tube Cover Banjo bolt
Number of modules	Max. 10 (with base for mounting on both sides) Max. 5 (with standard base) Max. 5
Connection to SmartWire-DT	No
Degree of protection	NEMA 13 NEMA 4X NEMA 4 IP66
Mounting Method	Floor Bracket Tube Horizontal
Mounting position	As required
Overvoltage category	III
Pollution degree	3
Product Category	SL signal towers
Rated impulse withstand voltage (Uimp)	4000 V AC
Shock resistance	Mechanical, According to IEC/EN 60068-2-27 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
Tube length	800 mm
Type	Base module
Ambient operating temperature - min	-30 °C
Ambient operating temperature - max	60 °C
Climatic proofing	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Terminal capacity (AWG)	24 - 16
Terminal capacity (flexible with ferrule and plastic collar)	0.25 - 0.75 mm^2
Terminal capacity (solid/flexible)	0.2 - 1.5 mm^2
Terminal capacity (solid/flexible with ferrule)	0.25 - 1.5 mm^2
Rated insulation voltage (Ui)	250 V
Rated operational voltage	110/120 V AC ± 10 % 24 V AC/DC ± 10 % 230/240 V AC ± 10 %

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Connection module for signal tower (EC001152)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Signal column element, connection module (ecl@ss10.0.1-27-37-12-32 [AKF050014])

Connection type auxiliary circuit			Spring clamp connection
Suitable for tube mounting			Yes
Suitable for bracket mounting			Yes
Suitable for floor mounting			Yes
Colour			Other
Suitable for AS interface			No

© 04/2023 by Eaton Industries GmbH