
PRODUCT-DETAILS

ZLS905E62-3L

Starter pack



General Information

Extended Product Type	ZLS905E62-3L
Product ID	2CCA183142R0001
EAN	7612271413750
Catalog Description	Starter pack
Long Description	Starter pack Touch proof with 62 Modules L1,L2,L3 Pluggable socket system SMISSLINE TP is completely □ngersafe (IP2XB) together with the socket end piece

Technical

Standards	IEC/EN 61439-6
Rated Operational Voltage	690 / 1000 V AC/DC
Rated Current (I_n)	125 A
Model Number	Flat
Surface Finishing	Tinned
Options Provided	3L

© 2024 ABB. All rights reserved.

Material Compliance

RoHS Information	9AKK107991A9646
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20170426
REACH Declaration	9AKK108467A9561
REACH Information	True - contains substances > 0.1 mass percentage
REACH Date	20230417
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental

Environmental Information	9AKK108467A9561

Dimensions

Product Net Width	111 mm
Product Net Height	1158 mm
Product Net Depth / Length	34 mm
Product Net Weight	1892 g
Dimension Diagram	9AKK107492A6192

Ordering

Package Level 1 Units	carton 1 piece
Package Level 1 Gross Weight	2018 g
E-Number (Switzerland)	809992810

Certificates and Declarations

Declaration of Conformity - CE	9AKK107991A9646

Installation

Instructions and Manuals	9AKK107680A2315

Popular Downloads

Data Sheet, Technical Information	9AKK107492A6192

Classifications


ETIM 8	EC001522 - Busbar
ETIM 9	EC001522 - Busbar

© 2024 ABB. All rights reserved.

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	85389030
eClass	V11.0 : 27370303
Object Classification Code	W

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Plug-in Distribution Systems → Plug-in Distribution Systems Accessories → Accessories for Plug-in Distribution Systems 125A



© 2024 ABB. All rights reserved.