SKYTEC | TRIGATA™

LIGHTWEIGHT CUT RESISTANT POLYURETHANE COATED GLOVE

A palm-dipped, lightweight glove offering level B cut resistance (EN 388:2016). The thin PU coating allows a secure grip in dry and light oily handling conditions. Ideal for precision handling when protecting against cuts.

FEATURES

- Cut resistant: Level B (EN 388:2016)
- Palm-coated polyurethane
- Lightweight 15 gauge liner
- Secure grip in dry and light oily handling environments
- Extremely hardwearing
- Soft and breathable liner
- Elasticated knitted wrist provides a secure and comfortable fit
- Excellent dexterity
- Sanitized® antimicrobial finish provides extra freshness



Sanitized Actifresh | CUT LEVEL B | LIGHTWEIGHT 15gg LINER

SUITABLE FOR

Typical Industries

- Aerospace
- Automotive
- Construction
- Engineering
- Glass
- Logistics
- Utilities

Suitable Applications

- Assembly
- Bottling/Canning
- Glass Manufacturing
- Handling of objects with sharp objects
- Maintenance
- Metal Fabrication
- Plastics Injection

CERTIFICATION

CAT II

CE

EN 388: 2016

3X42B

See overleaf for explanation

Globus GROUP

SKYTEC® | TRIGATA™

PRODUCT INFORMATION

MATERIALS	LINER:	15 gauge HPPE, glass fibre, nylon
	COATING:	Polyurethane (PU)
COLOUR	Blue	
LENGTH (mm)	250 (size dependent)	
CUFF STYLE	Elasticated knit wrist	

ORDERING DETAILS

SIZE	CODE	PACKAGING
6/XS 7/S 8/M 9/L 10/XL 11/XXL 12/XXXL	SKY900 SKY901 SKY902 SKY903 SKY904 SKY905 SKY906	10 pairs per bag 120 pairs per case

RECOMMENDATIONS FOR USE

- USE: General handling glove with cut protection. Not suitable for thermal, electrical and chemical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

CERTIFICATION LEGENDS

MECHANICAL HAZARDS EN 388:2016
PERFORMANCE LEVELS*

0-4 0-5 0-4 0-4 A-F P

- 0-4: Abrasion Resistance
- 0-5: Circular Blade Cut Resistance
- 0-4: Tear Resistance
- 0-4: Puncture Resistance
- A-F: Straight Blade Cut Resistance (EN ISO: 13997)
- P: Impact Resistance

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

EUROPE

www.globusgroup.com

E: sales@globus.co.uk
T: +44 (0)161 877 4747
F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com
T: +971 4 882 9962
F: +971 4 882 9963

Globus GROUP

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES

©2021 Globus (Shetland) Ltd | SKY-DATA-TRIGATA-0921_2

EU Type-Examination Certificate issued by SATRA Technology Europe Limited. Bracetown Business Park. Clonee. D15YN2P. Republic of Ireland. (Notified Body No. 2777)

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.