
LPCPA050


MONOBLOCK POTENTIOMETER Ø22MM PLATINUM SERIES, WITH GRADUATED SCALE 50KOHM



Product designation			Monoblock potentiometers
Product type designation			LPCPA
General characteristics			
Resistance value		Ω	50
Material			Polyamide - Resistive material: cermet
IEC degree of protection			IP66, IP67; IP96K on front and IP20 on rear
Electrical characteristics			
Rated insulation voltage Ui IEC/EN		V	250VAC
Rated impulse withstand voltage Uimp		kV	4
Max power		W	1
Mechanical features			
Mechanical travel		°	290
Weight		g	40
UL technical data			
UL degree of protection			1, 2, 3R, 4, 4X, 12, 12K on front
Ambient conditions			
Temperature			
	Operating temperature		
	min	°C	-25
	max	°C	+70
	Storage temperature		
	min	°C	-40
	max	°C	+85
Resistance & Protection			
Resistance tolerance		%	±10%


Dimensions





Wiring diagrams

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding



Certifications and compliance

Compliance	
	IEC/EN 60947-1
	IEC/EN 60947-5-1
Certificates	
	cULus

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding