Chemical protection

# ULTRANITRIL 358

Frequent contact | ultra-comfort wear

## Designed with an embedded optimal grip to safely handle tasks in dry & greasy environments




ADVANCED GRIP TECHNOLOGY

CHEMICAL PROTECTION
**TYPE A**

| EN388 | EN ISO 374-1 | EN ISO 374-5 |
|---|---|---|
| 3111A | TYPE A AJKOPT | |

| EN407 | | CATEGORY 3 |
|---|---|---|
| X1XXXX | ISO 18889 | 0334 |

| ISO 13997: | DEXTERITY |
|---|---|
| 4.9 N | EN ISO 21420: 5/5 |

## SPECIFIC ADVANTAGES

### Thermal protection

- Added comfort and thermal insulation, due to the cotton-knit lining

### Comfort

- Very supple glove providing high dexterity
- Good fingertips sensitivity

### Productivity

- Optimal grip to improve productivity, reduce hand fatigue and enhance safety

### Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

### Care for the environment

- Plastic packaging optimized
- Recycled material in the packaging: 30 %

## INDUSTRIES

- Automotive/mechanical industry
- Chemical industry
- Petrochemical industry
- Cosmetics and Pharmaceutical industry
- Agriculture sector

## APPLICATIONS

- Spray mixtures preparation
- Pesticides handling
- Tank filling
- Application & spreading of pesticides
- Pesticides waste management
- Treatment equipment cleaning
- Maintenance in wet environments (water, oil, greases, hydrocarbons)
- Chemical product blending
- Handling drums of chemical products
- Maintenance and handling

Edit 15/01/2025

MAPA SAS capital de 35.000.010 €
420, rue d'Estienne d'Orves
92705 Colombes Cedex France
RCS Nanterre 314 307 720

Chemical protection

# ULTRANITRIL 358

Frequent contact | ultra-comfort wear

## LEGENDS

EN388 — MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT TESTED)

| 3 | 1 | 1 | 1 | A | |
|---|---|---|---|---|---|
| 0-4 | 0-5 | 0-4 | 0-4 | A-F | P |

- P: Impact protection (optional)
- A-F: Cut resistance according to ISO 13997
- 0-4: Puncture resistance
- 0-4: Tear resistance
- 0-5: Blade cut resistance
- 0-4: Abrasion resistance

EN407 — THERMAL RISKS (HEAT AND FIRE)



PERFORMANCE LEVELS (X = NOT TESTED)

| X | 1 | X | X | X | X |
|---|---|---|---|---|---|
| 0-4 | 0-4 | 0-4 | 0-4 | 0-4 | 0-4 |

- 0-4: Resistance to large quantities of molten metal
- 0-4: Small splashes of molten metal
- 0-4: Radiant heat resistant
- 0-4: Convective heat resistance
- 0-4: Contact heat resistance
- 1: Limited flame spread

EN ISO 374-1



TYPE A

CHEMICAL RISKS
A: Methanol
J: n-Heptane
K: Sodium hydroxide 40%
O: Ammonia 25%
P: Hydrogen peroxide 30%
T: Formaldehyde 37%




ISO 18889

PROTECTION FROM PESTICIDES
G2: Diluted & concentrated pesticides / Mechanical risk

EN ISO 374-5



MICRO-ORGANISMS
Protection against bacteria and fungi

## PRODUCT DETAILS

| | |
|---|---|
| Interior finish | Textile support Mapa Technology |
| Exterior finish | Reinforced grip |
| Material | Nitrile |
| Colour.s | Green |
| Length (cm) | 36 |
| Thickness (mm) | 1,1 |
| European sizes | 6 7 8 9 10 11 |

## LOGISTIC DETAILS

| | |
|---|---|
| Packaging | 12 pairs/bag<br>72 pairs/carton |

## LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/05/24/1139
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 - Asqual 14 rue des Reculettes -75013 Paris - France

Edit 15/01/2025