
IGS205

IGB3012-BPKG/US-104 **Inductive sensors**



Made in Germany


Product characteristics		
Inductive sensor		
Metal thread M18 x 1		
Connector		
Increased sensing range		
Gold-plated contacts		
Sensing range 12 mm; [nf] non-flush mountable		
Electrical data		
Electrical design		DC PNP
Operating voltage	[V]	10...30 DC
Current consumption	[mA]	< 10
Protection class		II
Reverse polarity protection		yes
Outputs		
Output function		normally open
Voltage drop	[V]	< 2.5
Current rating	[mA]	100
Short-circuit proof		yes
Overload protection		yes
Switching frequency	[Hz]	300
Range		
Sensing range	[mm]	12
Real sensing range (Sr)	[mm]	12 ± 10 %
Operating distance	[mm]	0...9.72
Accuracy / deviations		
Correction factors		mild steel = 1 / stainless steel approx. 0.7 / brass approx. 0.5 / Al approx. 0.4 / Cu approx. 0.3
Hysteresis	[% of Sr]	3...15
Switch-point drift	[% of Sr]	-10...10
Environment		
Ambient temperature	[°C]	-25...70
Protection		IP 67
Tests / approvals		
EMC		EN 61000-4-2 ESD: 4 kV CD / 8 kV AD EN 61000-4-3 HF radiated: 10 V/m EN 61000-4-4 Burst: 2 kV EN 61000-4-6 HF conducted: 10 V EN 55011: class B
MTTF	[Years]	1528


IGS205

IGB3012-BPKG/US-104 **Inductive sensors**

Mechanical data		
Mounting		non-flush mountable
Housing materials		Brass white bronze coated; PBT; PEI; lock nuts: Brass
Weight	[kg]	0.045
Displays / operating elements		
Output status indication	LED	yellow (4 x 90°)
Electrical connection		
Connection		M12 connector

Wiring





Accessories		
Accessories (included)		2 lock nuts
Remarks		
Pack quantity	[piece]	1