PREVO S1 blow guns - ISO 6150 C profile - 6mm

CBG 06SIL

NEW

prevoS1 blow gun with composite nozzle



Technical characteristics

Profile:	**Max operating pressure:** 12 bar
Temperature: -15°C to +70°C	**Construction:** Polyamide composite body
Highlight: Compact	**Connection:** Built-in adaptor

prevoS1 coupler sold separately: CSI 06



A (mm)	B (mm)	Blowing force (at 6 bar (g))	Dynamic pressure (at 10 mm at 6 bar (bar))	Air consumption (at 6 bar (Nm3/h))	Sound level (at 6 bar (dBA))	Parts Numbers
113	97	165	0.2	9.4	74	**CBG 06SIL**

PREVOST UK - G, Tower Business Park, Commercial Rd, Darwen BB3 0FJ - United Kingdom
Tel. : (+44) 0844 800 2788 - Fax : (+44) 0844 800 2789 - E-mail : sales@prevost-ltd.co.uk - www.prevost.eu International = PREVOST SAS - - C.S. 90208 - 74942 ANNECY-LE-VIEUX CEDEX - France Tel. : +33 (4)50 64 04 45 - Fax : +33 (0)4 50 64 00 10 - E-mail : sales@prevost.eu- www.prevost.eu

This document is non-contractual. PREVOST reserves the right to modify the features of its range without prior notice.