PRODUCT-DETAILS

# E4.2V 2500 Ekip Dip LSIG 3p F HR

## E4.2V 2500 Ekip Dip LSIG 3p F HR



### General Information

| | |
|---|---|
| Extended Product Type | E4.2V 2500 Ekip Dip LSIG 3p F HR |
| Product ID | 1SDA071123R1 |
| EAN | 8015644749736 |
| Catalog Description | E4.2V 2500 Ekip Dip LSIG 3p F HR |
| Long Description | C.BREAKER SACE EMAX2 E4.2V 2500 FIXED THREE-POLE WITH TERMINALS REAR HORIZONTAL AND SOLID-STATE RELEASE IN AC EKIP/DIP-LSIG R 2500 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED |

### ABB EcoSolutions

| | |
|---|---|
| ABB EcoSolutions | Yes |
| Environmental Product Declaration - EPD | 9AKK108468A1904<br>9AKK108468A1910 |

### Material Compliance

| | |
|---|---|
| REACH Declaration | 9AKK108466A1425 |
| RoHS Information | 9AKK108466A1424 |

© 2024 ABB. All rights reserved.

| | |
|---|---|
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658 |
| Toxic Substances Control Act - TSCA | 9AKK108467A8326 |
| SCIP | d6a77472-7870-41be-a2fb-45c650173dd0 Italy (IT) |
| Simplified SCIP | 3e69484b-e30e-4b50-9fd7-2ad6eb8b9b04 Germany (DE)<br>fac2ac51-f936-4676-af1a-09f9c8b8346c Greece (GR)<br>59ab615a-030d-49a9-aa7e-cf60d28a73ec Estonia (EE)<br>fcbba79e-8fcb-4fc2-87dc-cf9102e6592a Sweden (SE)<br>4b6c006d-0362-4b60-87e4-60fc384ffe63 Germany (DE)<br>93e0e603-e475-42f7-8d68-a9f9d857214b Belgium (BE)<br>501f1b42-769b-45e5-95c5-e5fb5bd86aa5 Bulgaria (BG)<br>ddd90e81-dca0-4c49-92f8-de33b8fc6a8d Germany (DE)<br>cfc6137a-fdcf-4f19-bbe8-fa828af56906 Denmark (DK)<br>a6932c61-fcce-4d33-b01b-132078167178 France (FR)<br>6a21a9ba-fbb8-4c0e-8e05-8d00642d8020 Croatia (HR)<br>60fc5c02-da68-40e5-b1e5-f0eef24e4304 Germany (DE)<br>0f47dead-b275-4f6b-af3d-f1941fdfb832 Germany (DE)<br>91fd3b31-4f85-4f71-86e1-45608623139b Finland (FI)<br>0cafed6f-fe21-46b7-9c4a-2acc03093c33 France (FR)<br>fd51c1e1-b0cf-445d-9dfd-544f35ae1bac Netherlands (NL)<br>2ce23f30-84a9-498b-89b3-efe7457ff1e2 Poland (PL)<br>2a91ded6-ad0b-4126-a1fa-a954d7bb91a0 Norway (NO)<br>da2641cf-cdc7-4b76-ba3e-c11f7f6c8fcc Hungary (HU)<br>7bb5413e-d204-435e-a520-66ad71d921eb Poland (PL)<br>0d45ebd1-d8c0-4cc5-88b9-81d8a83f7ee3 Czech Republic (CZ)<br>759c0129-96b2-4eca-9f19-dd4574dbc8d6 Sweden (SE)<br>592dbdc3-ecda-4104-a71b-d7d826f0d573 Portugal (PT)<br>fd425ca7-18d9-44c0-a8f0-e9ea6b866217 Poland (PL)<br>795156c5-6121-4538-88a2-b21ca55dad76 Belgium (BE)<br>a0b1b850-9164-4e5f-9a5a-9c82bd0c2ff5 Spain (ES)<br>b60371d7-e353-4760-b757-1db186562983 Hungary (HU) |

## Environmental

| | |
|---|---|
| Environmental Information | 9AKK108467A6707 |

## Ordering

| | |
|---|---|
| Order Code US and Canada | Z4VUELBC000A000000XX |
| EAN | 8015644749736 |
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85362090 |

## Dimensions

| | |
|---|---|
| Product Net Width | 384 mm |
| Product Net Height | 371 mm |
| Product Net Depth / Length | 270 mm |
| Product Net Weight | 56 kg |

## Container Information

| | |
|---|---|
| Package Level 1 Units | box 1 piece |

© 2024 ABB. All rights reserved.

| | |
|---|---|
| Package Level 1 Width | 515 mm |
| Package Level 1 Height | 610 mm |
| Package Level 1 Depth / Length | 615 mm |
| Package Level 1 Gross Weight | 63 kg |
| Package Level 1 EAN | 8015644749736 |

## Additional Information

| | |
|---|---|
| Product Main Type | SACE Emax 2 |
| Product Name | Air Circuit Breaker |
| Product Type | Air Circuit Breaker |
| Version | F |
| CAD Dimensional Drawing | 1SDH001252R0171 |

## Technical

| | |
|---|---|
| Current Type | AC |
| Electrical Durability | Ue =< 440 V 8000 cycle<br>Ue = 500 ... 690 V 8000 cycle<br>20 cycles per hour |
| Mechanical Durability | 20000 cycle<br>60 cycles per hour |
| Number of Poles | 3P |
| Power Loss | 425 W |
| Rated Current ($I_n$) | 2500 A |
| Rated Impulse Withstand Voltage ($U_{imp}$) | acc. to IEC 60947-2 12 kV |
| Rated Insulation Voltage ($U_i$) | AC 1000 V |
| Rated Operational Voltage | 690 V AC |
| Rated Service Short-Circuit Breaking Capacity ($I_{cs}$) | (220 V AC) 150 kA<br>(230 V AC) 150 kA<br>(380 V AC) 150 kA<br>(400 V AC) 150 kA<br>(415 V AC) 150 kA<br>(440 V AC) 150 kA<br>(500 V AC) 100 kA<br>(660 V AC) 100 kA<br>(690 V AC) 100 kA |
| Rated Service Short-Circuit Breaking Capacity, in % of Icu ($I_{cs}$) | 100 % |
| Rated Short-time Withstand Current Low Voltage ($I_{cw}$) | for 1 s 100 kA<br>for 3 s 75 kA |
| Rated Ultimate Short-Circuit Breaking Capacity ($I_{cu}$) | (400 V AC) 150 kA<br>(415 V AC) 150 kA<br>(440 V AC) 150 kA<br>(500 V AC) 100 kA<br>(525 V AC) 100 kA<br>(690 V AC) 100 kA |
| Rated Uninterrupted Current ($I_u$) | 2500 A |
| Rated Voltage ($U_r$) | 690 V |
| Recommended Screw | Main Circuit M12 |

© 2024 ABB. All rights reserved.

| Driver | |
|---|---|
| Release | Ekip Dip LSIG |
| Release Type | EL |
| Short-Circuit Performance Level | V |
| Standards | IEC |
| Sub-type | E4.2 |
| Suitable for IT Networks | Yes, 690V |
| Terminal Connection Type | Rear flat Horizontal |
| Terminal Type | Bolt |
| Tightening Torque | 70 N·m |

## Certificates and Declarations

| | |
|---|---|
| ATEX Certificate | No certification needed |
| CSA Certificate | No certification needed |
| CSA Certificate (Intrinsic Safe) | No certification needed |
| Data Sheet, Technical Information | 1SDC200023D0209 |
| Declaration of Conformity - CE | 9AKK106713A5545 |
| UL Certificate | No certification needed |
| VDE Certificate | No certification needed |
| Mechanical Drawings | 1SDH001001R0100 |
| Wiring Diagram | 1SDM000091R0001 |
| Instructions and Manuals | 1SDH001000R0002 |

## Classifications

| | |
|---|---|
| ETIM 8 | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 9 | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| IDEA Granular Category Code (IGCC) | 4926 >> Air circuit breakers |
| Object Classification Code | Q |
| UNSPSC | 39121615 |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| eClass | V11.1 : 27370409 |

© 2024 ABB. All rights reserved.

## Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2



© 2024 ABB. All rights reserved.