Specifications

Eaton 193551

Catalog Number: 193551

Eaton Moeller series xPole - PXK RCBO - residual-current circuit breaker with overcurrent protection. RCBO B 25A 1+N 300mA sensitivity F



General specifications

Product Name	**Catalog Number**
Eaton Moeller series xPole - PXK RCBO - residual-current circuit breaker with overcurrent protection	193551
	EAN
	9010238026315
Product Length/Depth	**Product Height**
80 mm	75 mm
Product Width	**Product Weight**
35 mm	0.204 kg
Compliances	**Certifications**
CE Marked RoHS conform	CE

Powering Business Worldwide

Product specifications

Type

RCBO

Application

Switchgear for residential and commercial applications

Amperage Rating

25 A

Voltage rating

240 V - 240 V

Surge current capacity

3 kA

Voltage type

AC

Width in number of modular spacings

2

Features

Concurrently switching N-neutral

Anti-nuisance tripping version

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

Resources

Declarations of conformity

03_PXK-F_231017

DA-DC-03_PXK

03_PXK_231017

DA-DC-03_PXK-F

eCAD model

ETN.PXK-B25_1N_03-F.edz

Installation videos

xpole-pxkrcbo-installation-video

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Operating ambient temperature - max

40 °C

Operating ambient temperature - min

-25 °C

Product range

PXK

Rated current

25 A

Rated operational current for specified heat dissipation (In)

25 A

Rated switching capacity (IEC/EN 61009)

10 kA

Static heat dissipation, non-current-dependent

0 W

Tripping characteristic

B

Built-in depth

75.5 mm

Current limiting class

3

Rated short-circuit breaking capacity (EN 60947-2)

0 kA

Ambient operating temperature - max

40 °C

Ambient operating temperature - min

-25 °C

Fault current rating

0.3 A

Heat dissipation capacity

0 W

Heat dissipation per pole, current-dependent

0 W

Number of poles (protected)

1

Number of poles (total)

2

Rated operational voltage (Ue) - max

240 V

Rated short-circuit breaking capacity (IEC 60947-2)

0 kA

Rated switching capacity

10 kA

Basic function

Combined RCD/MCB devices

Rated impulse withstand voltage (Uimp)

4 kV

Degree of protection

IP20

Tripping

Short time delayed (10ms)

Overvoltage category

III

Pollution degree

2

Impulse withstand current

Surge-proof, 3 kA

Leakage current type

F

Release characteristic

B

Sensitivity type

Type F, pulse-current sensitive with frequency mixtures up to 1kHz

Frequency rating

50 Hz

Rated insulation voltage (Ui)

440 V

Connectable conductor cross section (solid-core) - min

1 mm²

Connectable conductor cross section (solid-core) - max

25 mm²

Connectable conductor cross section (multi-wired) - min

1 mm²

Connectable conductor cross section (multi-wired) - max

25 mm²

Rated short-circuit breaking capacity (EN 61009)

10 kA

Rated short-circuit breaking capacity (EN 61009-1)

10 kA

Number of poles

Single-pole + N

Disconnection characteristic

Undelayed

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia