Date: 24/04/2023

232.50.100 160 bar Diaphragm Seal lower mount

232.50.100 160 bar Séparateur vers le bas

Item number: 48223328

Quantity: 1 pcs.

Order code: DSS1-MT990.34-123X50-DZZZD-C7465ZA1-ZZAZZZZZ WAZ-Z
LABEL-PG1DE-ZZZZZ- ZZZZZ
232.50-E-BG516Z-CA-UZHZAZZ-ZZZZZZZ 213D31ZIXX0 Z2Z-IZZZZZZ12ZZZ
H990.34-P2MD8C1C2C1ZZZZZ 2 052H

Overview: 232.50.100 160 bar Diaphragm Seal lower mount
Measuring System 316L
Ingress protection: IP 65
class 1.0
Window: laminated safety glass
adjustable pointer
Pressure Gauge Standard: International (standard Europe)
WIKA
with Serial number

Diaphragm seal system with 1 diaphragm seal
Assembly specification High-Side: Direct assembly
System fill fluid: KN 2 Silicone oil for general applications
Process temperature min.: + 10°C
Process temperature max.: + 150°C
Ambient temperature pressure meas. min: + 10°C
Ambient temperature pressure meas. max: + 40°C

Welded design, threaded process connection
High-Side
Model 990.34 1/2" NPT male PN 160
Upper body material / main body material: Stainless steel 1.4404 (316L); UNS S31603
Diaphragm material: Stainless steel 1.4435 (316L); UNS S31603
Lower part material: Stainless steel 1.4404 (316L); UNS S31603
Diaphragm diameter: 52 mm

Label: WIKA standard without / with Tag-number

Details: 232.50.100 160 bar Séparateur vers le bas
Bourdon Tube Pressure Gauges, Stainless Steel
Version EN 837-1
Model: 232.50

© 2023 - WIKA Instruments s.a.r.l.

Specifications according to data sheet: PM 02.02
Measuring system: stainless steel
Case filling: without
Nominal size: 100 mm
Range: 0...160 bar
Process connection: diaphragm seal
Connector position: lower mount
Window: laminated safety glass
Pointer: adjustable pointer
Accuracy class: class 1.0
Material pressure element: Measuring System 316L
Pressure Gauge Standard: International (standard Europe)
Manufacturer logo: *WIKA*
serialnumber on dial: Serial number *...*
connected with
diaphragm seal, welded design,
with threaded process connection
Model: 990.34
Design: Welded design
Specifications according to data sheet: DS 99.04
Diaphragm diameter: 52 mm, max. 160 bar at +50°C
Process connection type: with threaded connection
Process connection: 1/2 NPT male
Material of wetted parts: stainless steel 316L
Process temperature: min.+10°C; max.+150°C
Ambient temperature: min.+10°C; max.+40°C
Assembly: direct assembly
System fill fluid: KN 2.2 Silicon oil
Diaphragm seal model: welded body with threaded connection
Reference temperature for diaphragm seal assembly: +21°C
height difference: no height difference
Bourdon Tube Pressure Gauges, Stainless Steel
Series
Model: 232.50
Specifications according to data sheet: PM 02.02
Measuring system: stainless steel
Case filling: without
Nominal size: 100 mm
Scale range: 0...160 bar
Process connection: Diaphragm Seal
Connector location: lower mount
Window: laminated safety glass
Pointer: adjustable pointer
Accuracy class: class 1.0
Overpressure safe: standard
Case material: Stainless steel 1.4301

© 2023 - WIKA Instruments s.a.r.l.

Case surface: bare
Material pressure element: Measuring System 316L
Case filling fluid: prepared for filling
Ingress protection: IP 65
Movement: stainless steel
Packaging: single packing
Pressure Gauge Standard: International (standard Europe)
Manufacturer logo: *WIKA*
with Serial number
Diaphragm seal system with 1 diaphragm seal
Assembly specification High-Side: Direct assembly
System fill fluid: KN 2 Silicone oil for general applications
Process temperature min.: + 10°C
Process temperature max.: + 150°C
Ambient temperature pressure meas. min: + 10°C
Ambient temperature pressure meas. max: + 40°C
Welded design, threaded process connection
Specifications according to data sheet: DS 99.04
High-/Low-Side: High-Side
Diaphragm seal: Model 990.34
Threaded connection: 1/2" NPT male
Nominal pressure rating: PN 160
Upper body material / main body material: Stainless steel 1.4404 (316L); UNS S31603
Diaphragm material: Stainless steel 1.4435 (316L); UNS S31603
Lower part material: Stainless steel 1.4404 (316L); UNS S31603
Diaphragm diameter: 52 mm

Label: WIKA standard without / with Tag-number

© 2023 - WIKA Instruments s.a.r.l.