Laserliner®



XXLCamera G3

ø 9 mm

5 m
DOF 1...6 cm

Universal micro camera for inspections over average distances

Rev 0617









Camera head (ø 9 mm) with LED-Lighting

– **Problem locating:** the camera indicates what is behind or in objects, walls circuits or cables etc. even under worst light conditions, due to the LED-lighting.
– **Ideal for difficult accessibly areas** due to the small measuring head (ø 9 mm)
– **Waterproof camera head and cable**
– Powerful object lighting thanks to **4 high-performance LEDs**

Only for VideoFlex G3.

TECHNICAL DATA
CAMERA HEAD / CABLE ø 9 mm, IP 68 (immersion depth 1,5 m, 60 min.)
CAMERA FOCUS F1 cm - F6 cm
CAMERA RESOLUTION 640 x 480 pixels
CABLE DIAMETER 6 mm
LENGTH OF FLEX CABLE 5 m
OPERATING TEMPERATURE 0 °C ... 45 °C
STORAGE TEMPERATURE -10 °C ... 60 °C
WEIGHT 650 g
DIMENSIONS (W x H x D) 5000 mm x 17 mm x 17 mm



XXLCamera G3
Packing dimension (W x H x D)
215 x 60 x 215 mm

ARTICLE	ARTICLE NO.	EAN CODE	PU
XXLCamera G3	082.219A	4 021563 698851	2

CAMERA 640 x 480 pixel LED LIGHT IP68

UMAREX GmbH & Co. KG · Donnerfeld 2 · 59757 Arnsberg · Germany · Tel. +49 2932 638-300 · Fax +49 2932 638-333 · laserliner@umarex.de · www.laserliner.com