Date: 11/04/2023

TG54.080/S, BM, 0...80°C , L1=100 mmx8mm

Model: TG54.080

Item number:	48801756
Quantity:	1 pcs.
Order code:	TG54.080BM-S-C1DZ-MI-C0100HZ-ZZZZ1ZZ TO F-1KD-AZ1ZZZZZ2ZZZZ CERT22-EF2T-FB- - - - - - - - - - -
Overview:	TG54.080/S, BM, 0...80°C , L1=100 mmx8mm Process connection: M20 x 1.5 laminated safety glass Ingress protection: IP 66 Permissible ambient temperature: -40 ... +70 °C *WIKA* with Serial number Test report 2.2 per EN 10204 Certificate Language: English and French Certificate for: thermometer mechanical Ingress protection: Ingress protection IP66
Details:	Model: TG54.080 Specifications according to data sheet: TM 54.02 Accuracy class: class 1 per EN 13190 Nominal size: 080 Connection location: back mount Connection design: standard, male thread Process connection: M20 x 1.5 Scale range: 0 °C ... 80 °C Stem diameter: 8 mm Insertion length L1: 100 mm Window: laminated safety glass Ingress protection: IP 66 Permissible ambient temperature: -40 ... +70 °C with Serial number Manufacturer logo: *WIKA* Test report 2.2 per EN 10204 Certificate Language: English and French Certificate for: thermometer mechanical Ingress protection: Ingress protection IP66

© 2023 - WIKA Instruments s.a.r.l.