Specifications

Eaton 292443



Catalog Number: 292443

Eaton xEnergy Basic LV systems Low voltage switchgear. Sheet steel door with rotary door handle HxW=1200x600mm, white

General specifications

Product Name	**Catalog Number**
Eaton xEnergy Basic door	292443
EAN	**Product Length/Depth**
4015082924430	45 mm
Product Height	**Product Width**
1210 mm	615 mm
Product Weight	**Compliances**
6.7 kg	RoHS conform

Powering Business Worldwide

Product specifications

Used with

Accessory
Service distribution board IVS
Accessory consideration
Wall-mounting distribution system

Special features

Closed
Mounting from front, fast mounting, hinges on left or right possible
Door opening angle 167°
1-point long with three-point turn-lock

Type

Additional equipment for wall-mounted service distribution board IVS

Accessory/spare part type

Doors

Surface finishing

Powder coating
With powder coating

Color

White
Traffic white (RAL 9016)

Degree of protection

IP30
NEMA Other

Unit type

Modular system

Suitable for height

1260 mm

Suitable for width

600 mm

Cover/door type

Three-point turn-lock

Material

Sheet steel
Steel

Resources

Brochures

eaton-xenergy-basic-light-brochure-br014024-en-us.pdf

Catalogs

eaton-distribution-boards-xenergy-basic-catalog-ca014010en-en-us.pdf

Declarations of conformity

DA-DC-03_xEnergy_Basic_BP

Sales notes

eaton-f3a-flange-flyer-fl019005en-en-us.pdf

Housing material

Sheet steel

Model

Stop door

Mounting method

Surface mounting

Functions

Wall-mounting distribution system

Additional equipment

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia