# 6958 - STUD BRANCH TEE POLYMER MALE BSPP SS 316L EPDM SEA




| | |
|---|---|
| **maximum working pressure** | 16 bar<br>2 MPa<br>232 psi |
| **working temperature** | -10 to 95 °C<br>14 to 203 °F<br>263 to 368 °K |
| **vacuum capability** | 755 mm Hg |
| **body** | BIO-BASED POLYMER |
| **sub-base** | STAINLESS STEEL 316L |
| **'O'-rings** | EPDM |
| **gripping ring** | STAINLESS STEEL |

• Convert to inch • Convert to oz • Reset Filters

| Part Nb | ØD (MM) | C | E (mm) | F (mm) | ØG (mm) | H (mm) | L_2 (mm) | (kg) |
|---|---|---|---|---|---|---|---|---|
| | All | All | All | All | All | All | All | All |
| 6958 04 10 | 4 | G1/8 | 5 | 13 | 8.5 | 22 | 14 | .009 |
| 6958 04 13 | 4 | G1/4 | 5.5 | 16 | 8.5 | 22 | 14 | .014 |
| 6958 06 10 | 6 | G1/8 | 5 | 13 | 10.5 | 28.5 | 16 | .011 |
| 6958 06 13 | 6 | G1/4 | 5.5 | 16 | 10.5 | 28.5 | 16 | .016 |
| 6958 08 10 | 8 | G1/8 | 4.5 | 13 | 13.5 | 38 | 23 | .019 |
| 6958 08 17 | 8 | G3/8 | 5.5 | 21 | 13.5 | 36 | 23 | .03 |
| 6958 10 13 | 10 | G1/4 | 5.5 | 16 | 16 | 43 | 26.5 | .032 |
| 6958 10 17 | 10 | G3/8 | 5.5 | 21 | 16 | 43 | 26.5 | .055 |
| 6958 10 21 | 10 | G1/2 | 7.5 | 24 | 16 | 43 | 26.5 | .051 |
| 6958 12 17 | 12 | G3/8 | 5.5 | 21 | 19 | 45.5 | 31 | .042 |
| 6958 12 21 | 12 | G1/2 | 7 | 24 | 19 | 45.5 | 31 | .049 |