Laserliner®



MicroCamera G3

ø 6 mm

1,5 m
DOF 1...6 cm

Universal micro camera with very small camera head and flexible cable

Rev 0617









Camera head (ø 6 mm) with LED-Lighting

- **Problem locating:** the camera indicates what is behind or in objects, walls circuits or cables etc. even under worst light conditions, due to the LED-lighting.
- **Ideal for difficult accessibly areas** due to the very small measuring head (ø 6 mm)
- **Waterproof camera head and cable**
- Powerful object lighting thanks to **4 high-performance LEDs**

Only for VideoFlex G3.

TECHNICAL DATA
CAMERA HEAD / CABLE ø 6 mm, IP 68 (immersion depth 1,5 m, 60 min.)
CAMERA FOCUS F1 cm - F6 cm
CAMERA RESOLUTION 640 x 480 pixels
CABLE DIAMETER 5 mm
LENGTH OF FLEX CABLE 1,5 m
OPERATING TEMPERATURE 0 °C ... 45 °C
STORAGE TEMPERATURE -10 °C ... 60 °C
WEIGHT 150 g
DIMENSIONS (W x H x D) 1500 mm x 17 mm x 17 mm



MicroCamera G3

Packing dimension (W x H x D)
190 x 10 x 180 mm

ARTICLE	ARTICLE NO.	EAN CODE	PU
MicroCamera G3	082.221A	4 021563 694938	2

CAMERA 640 x 480 pixel · LED LIGHT · IP68

UMAREX GmbH & Co. KG · Donnerfeld 2 · 59757 Arnsberg · Germany · Tel. +49 2932 638-300 · Fax +49 2932 638-333 · laserliner@umarex.de · www.laserliner.com