

MULTIMASTER MM 700 Max

Oscillating multi-tool – MM 700

Our best MultiTool for the most rapid work progress in interior work and renovation with a bimetal saw blade for wood, metal and plastics.

Product number: 7 229 68 63 00 0

Details

- Anti-vibration system: continuously safe and pleasant working thanks to minimal vibrations and outstanding noise insulation.
- StarlockMax tool mounting: more work progress and greater precision thanks to 100% power transmission without losses.
- QuickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system.
- With the StarlockMax tool mounting, you can access around 180 FEIN accessories from the Starlock, Starlock Plus and StarlockMax performance classes.
- 450 W FEIN high-power motor: high-power motor with a high copper content, which is suited to continuous use and overload for maximum cutting speed and the most rapid work progress.
- Tacho generator: constant speeds even under load and infinitely variable electronic speed control.
- Metal gearbox: ability to withstand high loading and outstanding service life because all the gearbox parts are made from metal.
- Mechanical interface: for stationary operation in the table or drill jig holder or for securing the depth stop.
- Industrial cable: large working radius thanks to finely stranded 5 metre rubber cable of industrial quality.
- Electronic safety cut-off – user protection should the saw blade lock, for example.
- Ideally equipped for every job. Mobile working with the L-BOXX system.

Price includes

- 1 Universal E-Cut saw blade (44 mm)
- 1 tool case (L-BOXX 136)

Product feature

- Mechanical interface

Technical data

TECHNICAL DATA

Input	450 W
Output	250 W
Oscillations	10,000 - 19,500 rpm
Tool Holder	StarlockMax
Tool change	QuickIN
Amplitude	2 x 2,0°
Cable with plug	5 m
Weight according to EPTA	1.60 kg
Weight according to EPTA	1.60 kg

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Uncertainty of measured value KpA	85 dB 3 dB
Sound power level LWA Uncertainty of measured value KWA	96 dB 3 dB
Sound peak value LpCpeak Uncertainty of measured value KpCpeak	97 dB 3 dB

Application examples








