Date: 11/04/2023

TW15-H 3/4NPT G 1/2 female U=550 mm B=0.260 inch (6.6 mm) SS316/316L

Threaded Thermowell TW15, solid machined

Item number:	48795198
Quantity:	1 pcs.
Order code:	TW15-H-B-M-NE-TD-00550-00045-G3-A-0160-0160-ZZ-ZZ00588 Z00588IZZZYQ2Z
Overview:	TW15-H 3/4NPT G 1/2 female U=550 mm B=0.260 inch (6.6 mm) SS316/316L Process thread [P or E]: 3/4NPT Connection to thermometer [N]: G 1/2 female Thermowell style: Straight Head length [H]: 45 mm Insertion length [U]: 550 mm Root diameter [Q]: 16 mm Tip diameter [V or F3]: 16 mm Bore size [B or d1]: 0.260 inch (6.6 mm) Bore depth / stem length (US) [A]: 588 mm Specifications according to data sheet: TW 95.15
Details:	Threaded Thermowell TW15, solid machined Specifications according to data sheet: TW 95.15 Head design: Hexagon Thermowell style: Straight Unit of measure: Metric (mm) Process thread [P or E]: 3/4 NPT Connection to thermometer [N]: G 1/2 female Insertion length [U]: 550 mm Head length [H]: 45 mm Material: Stainless steel 316/316L Bore size [B or d1]: 0.260 inch (6.6 mm) Root diameter [Q]: 16 mm Tip diameter [V or F3]: 16 mm Bore depth / stem length (US) [A]: 588 mm Tip thickness [Tt]: 0.250 inch (6.4 mm)

© 2023 - WIKA Instruments s.a.r.l.