Professionally approved products.

Datasheet

Long Coil Tubing Without Connector PUR 9 Bar

RS Stock number 224-209



Description:

Polyurethane tubing allows for small bend radii and compact installations.
Wide range of operating temperatures and pressures.
Excellent chemical resistance and ages well.
Hardness 52 ° Shore D.
Available in coils of 25m.
Good chemical resistance.
Constant rigidity, good ageing.
Good absorption of vibrations.
UV-resistance.
Fluid identification (crystal version).
Excellent Resistance to abrasion.
Silicone-free
Tube length marked every metre.

RS, Professionally Approved Products, gives you professional quality parts across all products categories. Our range has been testified by engineers as giving comparable quality to that of the leading brands without paying a premium price.

Professionally approved products.

Specifications:

Colour:	Blue
Manufacturer Series:	1025U
Material:	PUR
Maximum Operating Length:	25 m
Maximum Operating Pressure:	9 bar
Maximum Operating Temperature:	70 ^{0}C
Minimum Operating Temperature:	-15 ^{0}C
Tube Inside Diameter:	8 mm
Tube Outside Diameter:	12 mm

RS, Professionally Approved Products, gives you professional quality parts across all products categories. Our range has been testified by engineers as giving comparable quality to that of the leading brands without paying a premium price.