DISCONNECTABLE PEN SYSTEM



CERTIFICATIONS

RoHS

FEATURES

- Dedicated product allowing separation from PEN to PE+N
- Unique solution for TN-C/TN-S networks
- Safe disconnectable system
- Clear identification
- Prevents measurement errors
- Avoid reconnection errors
- Screen stickers included in 12 languages

SPECIFICATIONS

Complies With: IEC® 60439.1;IEC® 61439.1

Table 1/2

Catalog Number	Article Number	Max Current Rating, IEC	Thread Size (TS)	Busbar Width	Busbar Thickness	Depth (D)
PEN-D100	568805	250A	M8	0.79"	0.2"	2.69
PEN-D75	568800	125A	M6	0.59"	0.2"	2.69
PEN-D300	568810	630A	M10	1.18"	0.39"	3.08

Table 2/2					
Catalog Number	**Article Number**	**Height (H)**	**Width (W)**	**A**	**B**
PEN-D100	568805	6.69"	5.04"	3.94"	4.43"
PEN-D75	568800	4.72"	3.78"	3.94"	2.95"
PEN-D300	568810	6.69"	5.04"	3.94"	4.43"

DIAGRAMS





WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America
+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical Support

Europe
Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europe
Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC
Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500

Our powerful portfolio of brands:
nVent.com **CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER**

© 2025 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.