Specifications

Eaton 193523



Catalog Number: 193523

RCBO B 40A 1+N 100mA sensitivity F. FRBmM-B40/1N/01-F

General specifications

Product Name
Eaton Moeller series xEffect - FRBm6/M RCBO - residual-current circuit breaker with overcurrent protection

Catalog Number
193523

EAN
9010238026032

Product Length/Depth
80 mm

Product Height
75 mm

Product Width
35 mm

Product Weight
0.21 kg

Compliances
RoHS conform

Certifications
EN45545-2
IEC 61373

Powering Business Worldwide

Product specifications

Type

RCBO

Application

Switchgear for industrial and advanced commercial applications

Voltage rating

240 V - 240 V

Surge current capacity

3 kA

Voltage type

AC

Width in number of modular spacings

2

Features

Anti-nuisance tripping version

Concurrently switching N-neutral

Operating ambient temperature - max

40 °C

Operating ambient temperature - min

-25 °C

Rated current

40 A

Rated switching capacity (IEC/EN 60947-2)

10 kA

Built-in depth

75.5 mm

Current limiting class

3

Rated short-circuit breaking capacity (EN 60947-2)

10 kA

Ambient operating temperature - max

40 °C

Ambient operating temperature - min

-25 °C

Fault current rating

0.1 A

Resources

Brochures

xEffect_FR_RCCB_FAZ%20MCB.pdf

Catalogs

eaton-xeffect-frbm6-rcbo-catalog-ca003015en-en-us.pdf

Declarations of conformity

DA-DC-03_FRBM-1N

03_FRBM-F-1N_231017

03_FRBM-1N_191119

DA-DC-03_FRBM-F-1N

Drawings

eaton-xeffect-frbm6m-dimensions.jpg

eaton-xeffect-frbm6m-wiring-diagram.jpg

eaton-xeffect-frbm6m-characteristic-curve.jpg

eaton-xeffect-frbm6m-3d-drawing-006.jpg

eCAD model

ETN.FRBmM-B40_1N_01-F.edz

Installation videos

xeffect-FRBm6/M-installation-video

mCAD model

eaton-170541-drawing.dwg

eaton-170541-3d-model.stp

Number of poles (protected)

1

Number of poles (total)

2

Rated operational voltage (Ue) - max

240 V

Rated short-circuit breaking capacity (IEC 60947-2)

10 kA

Basic function

Combined RCD/MCB devices

Rated impulse withstand voltage (Uimp)

4 kV

Degree of protection

IP20

Overvoltage category

III

Pollution degree

2

Leakage current type

A

Release characteristic

B

Frequency rating

50 Hz

Rated insulation voltage (Ui)

500 V

Connectable conductor cross section (solid-core) - min

1 mm²

Connectable conductor cross section (solid-core) - max

25 mm²

Connectable conductor cross section (multi-wired) - min

1 mm²

Connectable conductor cross section (multi-wired) - max

25 mm²

Rated short-circuit breaking capacity (EN 61009)

10 kA

Rated short-circuit breaking capacity (EN 61009-1)

10 kA

Number of poles

Single-pole + N

Disconnection characteristic

Undelayed

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia