DATASHEET - M22-WRS-MS5-A1

Key-operated actuator, maintained, 2 positions, MS5, Key withdrawable: 0, Bezel: titanium

Part no. **M22-WRS-MS5-A1**
111786

Product name	Eaton Moeller® series M22 Key-operated actuator
Part no.	M22-WRS-MS5-A1
EAN	4015081113361
Product Length/Depth	70 millimetre
Product height	30 millimetre
Product width	30 millimetre
Product weight	0.034 kilogram
Certifications	UL Category Control No.: NKCR CSA File No.: 012528 UL UL 508 CE IEC/EN 60947 CSA-C22.2 No. 94-91 IEC/EN 60947-5 CSA Class No.: 3211-03 CSA CSA-C22.2 No. 14-05 UL File No.: E29184 VDE 0660
Product Tradename	M22
Product Type	Key-operated actuator
Product Sub Type	None
Catalog Notes	Key withdraw convertible with coding adapters M22-XC-... Not suitable for master key systems
Bezel color	Titanium
Bezel material	Plastic
Design	Key operated
Fitted with:	Front ring
Functions	Stay-put/spring-return function, can be changed with coding parts M22-XC-Y
Key code	MS5
Accessories	1 key included with supplied equipment.
Degree of protection	NEMA 4X, 13
Degree of protection (front side)	IP66
Lifespan, mechanical	100,000 Operations
Opening diameter	22.5 mm
Operating frequency	100 Operations/h
Operating torque	0.5 N·m
Product category	RMQ-Titan
Switching angle	60 °
Type	Key-operated button
Mounting position	As required
Shock resistance	Mechanical, According to IEC/EN 60068-2-27 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	70 °C
Climatic proofing	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30

Connection to SmartWire-DT		With SWD-RMQ connections Yes
Actuator color		Black
Actuator function		Switching function latching Key withdrawable in position 0 Maintained
Actuator type		Key
Number of switch positions		2
Force for positive opening - min		0 N
Equipment heat dissipation, current-dependent Pvid		0 W
Heat dissipation capacity Pdiss		0 W
Heat dissipation per pole, current-dependent Pvid		0 W
Rated operational current for specified heat dissipation (In)		0 A
Static heat dissipation, non-current-dependent Pvs		0 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Please enquire
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		Not applicable.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Front element for selector switch (EC000222)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for selector switches (ecl@ss10.0.1-27-37-12-13 [AKF031014])

Number of switch positions		2
Type of control element		Key
Suitable for illumination		No
Colour control element		Black
Colour indicator light cap		Other
Construction type lens		Round
Hole diameter	mm	22.5
Width opening	mm	0
Height opening	mm	0
Switching function latching		Yes
Spring-return		No
With front ring		Yes

Material front ring			Plastic
Colour front ring			Titanium
Degree of protection (IP), front side			IP66
Degree of protection (NEMA)			4X, 13

© 04/2023 by Eaton Industries GmbH