Specifications

Eaton 199425

Catalog Number: 199425

Eaton DC1 Variable frequency drive, 230 V AC, 3-phase, 30 A, 7.5 kW, IP66/NEMA 4X, Radio interference suppression filter, Brake chopper, 7-digital display assembly, Additional PCB protection, UV resistant, FS4



General specifications

Product Name
Eaton DC1 Variable frequency drive

Catalog Number
199425

EAN
4015081978144

Product Length/Depth
275 mm

Product Height
360 mm

Product Width
240 mm

Product Weight
9.5 kg

Certifications
EAC
IEC/EN 61800-5-1
CE marking
IEC/EN61800-5
UL File No.: E172143
UL 508C
CUL
UkrSEPRO
UL Listed
CSA-C22.2 No. 14
IEC/EN 61800-2
IEC/EN 61800-3
UL report applies to both US and Canada
Certified by UL for use in Canada
RoHS, ISO 9001
CE

Powering Business Worldwide

UL

RCM

U

NMMS7

Features & Functions

Features

Parameterization: drivesConnect mobile (App)

Parameterization: Keypad

Parameterization: Fieldbus

Parameterization: drivesConnect

Fitted with:

IGBT inverter

Brake chopper

7-digital display assembly

Additional PCB protection

Breaking resistance

Control unit

Internal DC link

PC connection

UV resistance

Radio interference suppression filter

Functions

4-quadrant operation possible

Catalog Notes

Environmental class: 3C3, 3S3

Overload cycle for 60 s every 600 s

For normal internally and externally ventilated four-pole three-phase asynchronous motors with 1500 rpm at 50 Hz and 1800 rpm at 60 Hz

General

Cable length

C2 ≤ 5 m, maximum motor cable length

100 m, screened, maximum permissible cable length

300 m, unscreened, with motor choke, maximum permissible, Motor feeder

C3 ≤ 25 m, maximum motor cable length

150 m, unscreened, maximum permissible cable length

200 m, screened, with motor choke, maximum permissible cable length

Communication interface

SmartWire-DT, optional

OP-Bus (RS485), built in

CANopen®, built in

Modbus RTU, built in

Connection to SmartWire-DT

No

Degree of protection

IP66

NEMA 4X

Climatic environmental conditions

Altitude

Above 1000 m with 1 % derating per 100 m

Max. 4000 m

Ambient operating temperature - min

-20 °C

Ambient operating temperature - max

40 °C

Ambient storage temperature - min

-40 °C

Ambient storage temperature - max

60 °C

Climatic proofing

< 95 average relative humidity (RH), no condensation, no corrosion

Main circuit

Electromagnetic compatibility

1st and 2nd environments (according to EN 61800-3)

Frame size

FS4

Mounting position

Vertical

Product category

Variable frequency drives

Protection

Finger and back-of-hand proof, Protection against direct contact (BGV A3, VBG4)

Protocol

Other bus systems
MODBUS
EtherNet/IP
CAN

Radio interference class

Optional external radio interference suppression filter for longer motor cable lengths and for use in different EMC environments C2, C3: depending on the motor cable length, the connected load, and ambient conditions. External radio interference suppression filters (optional) may be necessary.

Suitable for

Branch circuits, (UL/CSA)

Efficiency

97 % (η)

Heat dissipation capacity Pdiss

0 W

Input current ILN at 150% overload

33.3 A

Leakage current at ground IPE - max

6.9 mA

Mains switch-on frequency

Maximum of one time every 30 seconds

Mains voltage - min

200 V

Mains voltage - max

240 V

Operating mode

Speed control with slip compensation
BLDC motors
PM motors
Sensorless vector control (SLV)
Synchronous reluctance motors
U/f control

Output frequency - min

0 Hz

Output frequency - max

500 Hz

Output voltage (U2)

240 V AC, 3-phase
230 V AC, 3-phase

Overload current IL at 150% overload

45 A

Rated control supply voltage

10 V DC (Us, max. 10 mA)

Rated frequency - min

48 Hz

Rated frequency - max

62 Hz

Rated operational current (Ie)

30 A at 150% overload (at an operating frequency of 6 kHz and an ambient air temperature of +40 °C)

Rated operational voltage

230 V AC, 3-phase

240 V AC, 3-phase

Resolution

0.1 Hz (Frequency resolution, setpoint value)

Short-circuit protection rating

45 A, UL (Class CC or J), Safety device (fuse or miniature circuit-breaker), Power Wiring

Starting current - max

175 % IH

Supply frequency

50/60 Hz

Switching frequency

8 kHz, 4 - 24 kHz adjustable (audible), fPWM, Power section, Main circuit

System configuration type

AC supply systems with earthed center point

Voltage rating - max

240 V

Motor rating

Assigned motor current IM at 110/120 V, 60 Hz, 150% overload

30 A

Assigned motor current IM at 115 V, 50 Hz, 150% overload

30 A

Assigned motor current IM at 220 - 240 V, 60 Hz, 150% overload

30 A

Assigned motor current IM at 230 V, 50 Hz, 150% overload

30 A

Assigned motor current IM at 400 V, 50 Hz, 150% overload

30 A

Assigned motor current IM at 440 - 480 V, 60 Hz, 150% overload

30 A

Assigned motor power at 115/120 V, 60 Hz, 1-phase

10 HP

Assigned motor power at 230/240 V, 60 Hz, 1-phase

10 HP

Assigned motor power at 460/480 V, 60 Hz

10 HP

Assigned motor power at 460/480 V, 60 Hz, 3-phase

10 HP

Apparent power

Apparent power at 230 V

6.9 kVA

Apparent power at 240 V

7.2 kVA

Braking function

Braking resistance

15 Ω

Braking torque

Max. 100 % of rated operational current Ie, variable, DC - Main circuit

Switch-on threshold for the braking transistor

390 VDC

Control circuit

Number of inputs (analog)

2 (parameterizable, 0 - 10 V DC, 0/4 - 20 mA)

Number of inputs (digital)

Design verification

Heat dissipation capacity Pdiss

0 W

Heat dissipation per pole, current-dependent Pvid

4 (parameterizable, 10 - 30 V DC)

Number of outputs (analog)

1

Number of outputs (digital)

1

Number of relay outputs

1 (parameterizable, N/O, 6 A (250 V, AC-1) / 5 A (30 V, DC-1))

0 W

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Resources

Application notes

Motor data - Motor Protection - V/f curves Slip Compensation

The OP System Bus - Parameterizing - Control

Conformal Coating

Dependency of the output current on switching frequency and ambient temperature

DX-COM-STICK3_Connection

Operating Permanent Magnet and Brushless DC Motors

I/O Configuration

PI controller

Low Temperature Applications

Operating Single Phase Motors

Connecting drives to generator supplies

Fire Mode

Set Point Setting

Starting, Stopping and Operation

How does the internal motor protection work?

Electromagnetic compatibility (EMC)

Access to Parameter Levels 2 + 3 Parameter Lock - Load Default

Update DX-COM-STICK3

Brochures

eaton-powerxl-variable-frequency-drives-dc1-da1-brochure-br040001en-en-us.pdf

DA-SW-drivesConnect

Catalogs

Product Range Catalog Drives Engineering

Declarations of conformity

DA-DC-00004555.pdf

DA-DC-00004184.pdf

DA-DC-00004552.pdf

DA-DC-00003964.pdf

Drawings

eaton-frequency-inverter-dc1-dimensions-008.eps

Installation instructions

eaton-powerxl-dc1-ip66-instruction-leaflet-il040059zu.pdf

Installation videos

Video PowerXL DA1

PowerXL Variable Frequency Drives DC1 and DA1 - EN

Manuals and user guides

MN040018_EN

MN040022_EN

MN040059_EN

eaton-canopen-communication-manual-for-variable-frequency-drives-variable-speed-starters-da1-db1-dc1-de11-mn040019-en-us.pdf

MN040003_EN

mCAD model

e3_s4_ip66_ohne_bedienelementen.dwg

e3_s4_ip66_ohne_bedienelementen.stp

Multimedia

Looking for variable frequency drives DC1 and DA1 which can be used in harsh environments?

Product notifications

eaton-drives-ecodesign-directive-mz040046en-en.pdf

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia