

Part Number: 9728

RS232/422 Low Cap, #24-4pr, FPO, Indiv. Foil, PVC Jkt, CM, 100Ω

Product Description

Computer EIA RS-232/422, Digital Audio Cable, 24 AWG stranded (7x32) tinned copper conductors, Datalene® insulation, twisted pairs, individually Beldfoil® shielded (100% coverage) each with 24 AWG stranded tinned copper drain wire, overall PVC jacket.

Technical Specifications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	Nominal Diameter	No. of Conductors	No. of Pairs
24	7x32	TC - Tinned Copper	0.024 in	8	4

Conductor Count:	8
Total Number of Pairs:	4
Conductor Size:	24 AWG

Insulation

Material	Material Trade Name	Nominal Wall Thickness
FPE - Foamed Polyethylene	Datalene®	0.019 in

Color Chart

Number	Color
1	Black & Red
2	Black & White
3	Black & Green
4	Black & Blue

Inner Shield Material

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Aluminum Foil-Polyester Tape	Beldfoil® (Z-Fold®)	100 %	TC - Tinned Copper	24	7x32

Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.363 in	0.048 in

Electrical Characteristics

Conductor DCR

Individual Pair Nominal Shield DCR	Nominal Conductor DCR
15 Ohm/1000ft	24 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
12.5 pF/ft	23.2 pF/ft

Inductance

Nominal Inductance
0.23 µH/ft

Impedance

Nominal Characteristic Impedance
100 Ohm

High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
0.384 MHz	0.74 dB/100ft
0.7056 MHz	0.87 dB/100ft
0.768 MHz	0.88 dB/100ft
1.024 MHz	0.94 dB/100ft
1.4112 MHz	1.01 dB/100ft
1.536 MHz	1.03 dB/100ft
2.048 MHz	1.13 dB/100ft
2.8224 MHz	1.29 dB/100ft
3.072 MHz	1.35 dB/100ft
4.096 MHz	1.57 dB/100ft
5.6448 MHz	1.78 dB/100ft
6.144 MHz	1.84 dB/100ft
8.192 MHz	2.13 dB/100ft
11.2896 MHz	2.45 dB/100ft
12.288 MHz	2.57 dB/100ft
24.576 MHz	3.57 dB/100ft

Delay

Max. Delay Skew	Nominal Velocity of Propagation (VP) [%]
76 ns/100m	76 %

High Freq

Frequency [MHz]
0.384 MHz
0.7056 MHz
0.768 MHz
1.024 MHz
1.4112 MHz
1.536 MHz
2.048 MHz
2.8224 MHz
3.072 MHz
4.096 MHz
5.6448 MHz
6.144 MHz
8.192 MHz
11.2896 MHz
12.288 MHz
24.576 MHz

Current

Max. Recommended Current [A]
Per conductor @ 25°C: 2.5 A

Voltage

UL Description	UL Voltage Rating
UL AWM Style 2493	300 V RMS

Temperature Range

UL Temp Rating:	80°C (UL AWM Style 2919)
Operating Temp Range:	-20°C To +80°C

Mechanical Characteristics

Bulk Cable Weight:	51 lbs/1000ft
Max Recommended Pulling Tension:	65 lbs

Min Bend Radius/Minor Axis:	3.75 in

Standards

NEC Articles:	800
NEC/(UL) Specification:	CM
CEC/C(UL) Specification:	CM
UL AWM Style:	2919 (30 V 80°C)
CPR Euroclass:	Eca

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1685 UL Loading
UL voltage rating:	300 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	89728

Part Number

Variants

Item #	Color	Footnote
9728.001524	Chrome	
9728.0030	Chrome	
9728.00305	Chrome	
9728.01152	Chrome	
9728 060100	Chrome	
9728 0601000	Chrome	C
9728 060500	Chrome	
9728 0605000	Chrome	

Footnote:	C - CRATE REEL PUT-UP.

Product Notes

Notes:	Datalene® insulation features include low dielectric constant and a dissipation factor for high-speed, low-distortion data handling. Physical properties include good crush resistance and light weight.

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.