

CCG 18-125-7 AS

Cordless angle grinder, 125 mm in diameter

Compact and easy-to-use cordless angle grinder for light-duty grinding and cutting work.

Product number: 7 122 13 61 00 0

Details

- High power, mobile use: The brushless high-power motor delivers the same power as a comparable corded 700 W tool for light-duty grinding and cutting work.
- Optimum user protection features include restart protection, soft start and electronic overload protection.
- Slimline handle and balanced design for perfect ergonomics.
- Secure hold for all applications thanks to non-slip handle.
- Safety hood, which can be adjusted without the use of tools, and quick-clamping nuts make for short setup times.
- Compatible with all 18 V AMPShare ProCORE batteries and chargers for even more power and flexibility. Also suitable for 18 V Bosch Professional cordless devices.
- COOLPACK 2.0 technology delivers a 135% longer battery life and therefore makes longer operating times possible.
- State-of-the-art cell technology and intelligent battery management deliver 87% more power than with conventional batteries.
- ProCORE Li-Ion battery with high-power cells, charge status indicator and “Electronic Cell Protection” (ECP). ECP protects against overload, overheating and total discharge.
- Ideally equipped for every form of use. Mobile working with the L-BOXX system.

Price includes

- 1 Tool-free quick-clamping nut
- 1 wheel guard
- 1 safety hood for cutter
- 1 Inner flange
- 1 anti-vibration handle
- 1 tool case (L-BOXX 136)

Product feature

- POWERtronic tacho electronics
- Restart protection
- Soft start
- Electronic overload protection

Application

Deburring	++
Dividing	++
Brushing	+

\+ suitable
++ well suitable

Technical data

TECHNICAL DATA

Speed, no load	11,000 rpm
Grinding disc Ø	125 mm
Elast. Backing pad Ø	125 mm
Flange	M 14

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Uncertainty of measured value KpA	79 dB 3 dB
Sound power level LWA Uncertainty of measured value KWA	90 dB 3 dB
Vibration value 1 αhv 3-way Uncertainty of measured value Kα	7,0 m/s² 1,5 m/s²
Vibration value 2 αhv 3-way Uncertainty of measured value Kα	3,5 m/s² 1,5 m/s²

Application examples



Kompatibel mit AMPShare-/ Bosch Professional 18 V Akkus. | Compatible with AMPShare/Bosch Professional 18 V batteries. | Compatible avec les batteries 18 V AMPShare/Bosch Professional. | Compatible con baterías AMPShare/Bosch Professional de 18 V. | Compatibile con le batterie AMPShare / Bosch Professional da 18 V.